



B (1:2)



\*) MEASURING FORCE IF THE GAUGE IS HELD IN MEASURING POSITION AS SHOWN ABOVE

subject to technical alterations

<b>type:</b>	<b>Modul 2</b>
<b>range:</b>	<b>0 - 100 mm</b>
<b>range of indication:</b>	<b>0 - 101 mm</b>
<b>digital step:</b>	<b>-</b>
<b>scale interval:</b>	<b>0,1 mm</b>
<b>measuring force:</b>	<b>1,2 - 1,8 N *)</b>
<b>weight:</b>	<b>1,1 kg</b>

<small>acceptable deviations VDI/VDE/DGQ 2618 Bl. 12.1/13.1)</small>	
<b>max. permissible errors "G":</b>	<b>0,3 mm</b>
<b>repeatability "r":</b>	<b>0,2 mm</b>
<b>reference temperature:</b>	<b>20° C</b>
<b>operation temperature:</b>	<b>10° C - 30° C</b>
<b>storage temperature:</b>	<b>-10° C - 50° C</b>

<b>scale:</b>	<b>1:5 (1:2)</b>
<b>drawing-nr.:</b>	<b>DAB-D12100T_KR_e</b>
<b>date of issue:</b>	<b>27.03.2015</b>
<b>name:</b>	<b>J.Röder</b>
<b>revision status:</b>	
<b>revision date:</b>	