Mitutoyo



Small Tool Instruments and Data Management | Form Measurement | Digital Scales and DRO Systems

Sensor Systems | Test Equipment | Optical Measurement | Vision Measuring Systems

FALL PROMO 2026

PRECISION TOOLS & INSTRUMENTS

Effective September 21 through December 18

FALL PROMO 2026



Bulletin No. 2399(P)

Mitutoyo

NEW FEATURED
PRODUCTS

FALL PROMO 2026













TABLE OF CONTENTS

MDE QuantuMike 6
The new MDE QuantuMike delivers faster measurements - up to 4x faster than standard micrometers - with exceptional accuracy (±1 µm permissible error), an IP65 protection rating, and a user-friendly design with enhanced display.

LH-600F Linear Height Gages 10
The Mitutoyo LH-600F Linear Height Gage is the latest model in the line with several new features like an adjustable and rotatable display, intuitive touchscreen interface, and added output options for even easier, highly accurate 1D and 2D dimensional measurements.

ID-C/ID-F Digimatic Indicators 14
The new Digimatic Indicators have higher resolutions down to 20 µinch/0.5 µm, a built-in calibration date warning and analog bar on the larger LCD display, and new S1 Digimatic output capabilities.

Profile Projectors 22
Mitutoyo profile projectors provide some of the most accurate and clear images on the market. Easily capture accurate measurements without blurring, distortion or complex calculations using our modular 2D digital readouts.

QM-Fit 24
The new QM-Fit is an all-in-one smart measurement system that delivers fast, effortless results. Automatic element detection instantly recognizes a workpiece, identifies features, and performs the measurement.

Surftest SJ-220 30
Mitutoyo surface roughness testers are highly versatile and deliver precise, accurate measurements across a wide range of applications, including portable models.

Calipers 4
Calipers/Caliper Checker 5
QuantuMike/QuickMike 6
Micrometers 7
Tool Kits 8,9
LH-600F Height Gage 10
QM Height Gage 11
Dial Indicators 12
Bore Gages 12
Dial Test Indicators 13
Indicators 14,15
Specialized Indicators 16
Borematic 17
Holtest 18, 19
Bluetooth® + Wireless Data Transmitters 20
U-WAVE Wireless Data Transmitters 21
Profile Projectors 22,23
QM-Fit 24,25
Quick Image 26,27
Microscopes 28,29
Surftest SJ-220 30,31
Hardness Testers 32,33, 34, 35
Linear Gages/EJ Counters 36, 37
Litematic Units 38
Laser Scan Micrometers 39
Linear Encoders for Lathes, Grinders, and Mills 40
Digimatic Scales 41
The Mitutoyo Advantage 42, 43

MRM™

MRM Metrology Inc.
905 595 1000
sales@MRMmetrology.com
www.MRMmetrology.com


Scan to see many more great offers

In-Stock Calibrated Tools

Order No.	Description	List	Promo
293-330-32DCAL	Micrometer, Digimatic 0-1", .00005"/0-25.4mm, 0.001mm, SPC, IP65, W/Certificate	$432.00	$384.00
293-340-30DCAL	Micrometer, Digimatic 0-1", .00005" / 0-25.4mm, 0.001mm, IP65, W/Certificate	$402.00	$358.00
500-171-30DCAL	Caliper, Digimatic Encoder Technology 0-6", .0005" / 0-150mm, 0.01mm, SPC, W/Certificate	$342.00	$263.00
500-171-32DCAL	Caliper, Digimatic Encoder Technology 0-6", .0005" / 0-150MM, 0.01MM, SPC, W/Certificate	$345.00	$273.00
500-172-32DCAL	Caliper, Digimatic Encoder Technology 0-8", .0005"/0-200MM, 0.01MM, SPC, W//Certificate	$466.38	$393.00
500-173-30DCAL	Caliper, Digimatic Encoder Technology 0-12", .0005" / 0-300mm, 0.01mm, SPC, W/Certificate	$790.82	$632.00
500-193-30DCAL	Caliper, Digimatic Encoder Technology 0-12", .0005" / 0-300mm, 0.01mm, W/Certificate	$736.00	$588.80
500-196-30DCAL	Caliper, Digimatic Encoder Technology 0-6", .0005" / 0-150mm, 0.01mm, W/Certificate	$304.00	$263.00
500-196-32DCAL	Caliper, Digimatic Encoder Technology 0-6", .0005" / 0-150MM, 0.01MM, W/Certificate	$304.00	$273.00
500-197-30DCAL	Caliper, Digimatic Encoder Technology 0-8", .0005" / 0-200mm, 0.01mm, W/Certificate	$410.23	$369.00
500-197-32DCAL	Caliper, Digimatic Encoder Technology 0-8", .0005" / 0-200MM, 0.01MM, W/Certificate	$442.38	$393.00
500-752-20DCAL	Caliper, Digimatic 0-6", .0005" / 0-150mm, 0.01mm IP67, W/Certificate	$362.65	$290.00
500-753-20DCAL	Caliper, Digimatic, 0-8", .0005" / 0-200mm, 0.01mm, IP67, W/Certificate	$485.48	$388.00
500-754-20DCAL	Caliper, Digimatic 0-12", .0005" / 0-300mm, 0.01mm IP67, W/Certificate	$697.30	$557.00
505-743JDCAL	Caliper, Mechanical, Dial , 0-8", .001" W/Certificate	$371.00	$333.00
505-746DCAL	Caliper, Mechanical, Dial, 0-12", .001" W/Certificate	$543.00	$488.00
543-783B-10DCAL	Indicator, Digimatic, ID-S .5", .0005" / 12.7mm, 0.01 mm, SPC, W/Certificate	$340.00	$306.00

Digimatic Calipers


› AOS Electromagnetic inductive sensor improves environmental resistance against dirt, water and oil.



500-171-30-DCAL

Coolant-Proof Calipers

› Sealed housing is IP67 rated, meaning it's resistant to the coolants, dirt, grit and chips found in many manufacturing environments.



500-752-20-DCAL

Digimatic Indicator

› Range: .5" / 12.7mm

› Resolution: .005" / 0.01mm

› SPC Output



543-783B-10DCAL

Digimatic Micrometer

› Range: 1"

› Resolution: .00005" / 0.001mm

› Features include: preset, Zero/ABS mode, Function Lock and more



293-330-30-DCAL

Dial Calipers


› Smooth sliding with high shock protection.



505-743J-DCAL

Digimatic Calipers

MeasurLink® ENABLED
Data Management Software by Mitutoyo



500-171-30

SPC

ABSOLUTE
Absolute System Patented by MITUTOYO

ABSOLUTE AOS DIGIMATIC

AOS: Advanced Onsite Sensor

- AOS Electromagnetic Inductive Sensor improves environmental resistance against dirt, water and oil.
- A battery life of approximately 3.5 years has been achieved under normal use through the adoption of the Mitutoyo ABSOLUTE scale.
- The slider configuration features an ergonomic, thumb-friendly shape.
- Step-measurement capable.
- The data output function allows integration into Statistical Process Control and measurement systems.
- Display character height: 9mm.
- AOS applies to 4", 6" and 8" models.
- Resolution: .0005"/0.01mm.

OUTPUT MODELS ARE PRICED LOWER THAN NON-OUTPUT MODELS


Order No.	Range	Remarks	List	Promo
No SPC Output Style				
500-195-32	0-4"/0-100mm	.075" Round Depth Bar	$227.00	
500-196-32	0-6"/0-150mm		$246.00	
500-197-32	0-8"/0-200mm		$355.00	
500-193-30	0-12"/0-300mm		$711.00	
With SPC Output Style				
fit 500-170-32	0-4"/0-100mm	.075" Round Depth Bar	$271.00	**$218.00**
fit 500-171-32	0-6"/0-150mm		$288.00	**$236.00**
fit 500-172-32	0-8"/0-200mm		$379.00	**$341.00**
fit 500-173-30	0-12"/0-300mm		$830.00	**$683.00**
500-505-10	0-18"/0-450mm	Without Thumb Roller	$1,289.00	
500-506-10	0-24"/0-600mm	Without Thumb Roller	$1,423.00	
500-507-10	0-40"/0-1000mm	Without Thumb Roller	$2,748.00	

fit U-WAVE-Fit compatible

SPC cable with data switch – 1m: **959149** 2m: **959150**

Order Numbers are subject to change, e.g. **500-196-30** will change to **500-196-32**

Dial Caliper



505-742-56J

- Smooth sliding with high shock protection.
- Lock screw for dial bezel and for holding the sliding jaw position.
- Can measure OD, ID, depth and steps.
- Models available with carbide-tipped OD and ID jaws.

Order No.	Range	Remarks	List	Promo
505-742J	0 -6" .100"/rev		$199.00	$191.00
505-743J	0 -8" .100"/rev		$291.00	$279.00
505-738	0 -6" .100"/rev	Carbide-tipped jaws	$357.00	$343.00
505-740J	0 -6" .200"/rev		$182.00	$175.00
505-746	0 -12" .100/rev		$443.00	$425.00
505-749	0 -12" .200/rev		$413.00	$396.00
505-742-56J	0 -6" .100"/rev	Black Dial Face	$199.00	$191.00

THE MITUTOYO ADVANTAGE

Whatever your challenges are, Mitutoyo Canada supports you from start to finish. Mitutoyo is not only a manufacturer of top-quality measuring products but one that also offers quality support and services that last throughout your products' lifetime. Apart from the basics of calibration and repair, we offer product & metrology training, software support, as well as contract inspection and programming services.

The Mitutoyo Advantage includes:

- Consistently high-quality products, software, solutions, and accessories
- Industry-leading local Service & Support with FAST turnaround times
- Decreased wait time with the Expedited Services and the Calibrated Tools program using our in-house Repair & Calibration Departments
- Accredited Calibration, Performed at Your Facility for Your Small Tools
- Easy access to our Contract Inspection and Programming Services as well as our Custom Solution team



Coolant-Proof Calipers



- Sealed housing is IP67 rated, meaning it's resistant to coolants, dirt, grit and chips found in many manufacturing environments.
- Easy to use - no need to wipe or clean the scale.
- .0005"/0.01mm resolution with ±.001" accuracy.
- Automatic power On/Off.
- Certificate of Inspection provided.

OUTPUT MODELS ARE PRICED LOWER THAN NON-OUTPUT MODELS

Order No.	Range	List	Promo
Non-Output Style			
500-752-20	0-6"/0-150mm	$330.00	
500-753-20	0-8"/0-200mm	$441.00	
500-754-20*	0-12"/0-300mm	$764.00	
SPC Output Style			
fit 500-762-20	0-6"/0-150mm	$390.00	$317.00
fit 500-763-20	0-8"/0-200mm	$492.00	$423.00
fit 500-764-20*	0-12"/0-300mm	$847.00	$733.00

* ±.0015" accuracy fit U-WAVE Fit compatible SPC cable – 1m: **05CZA624** 2m: **05CZA625**

COMPATIBLE WITH U-WAVE fit

MeasurLink ENABLED Data Management Software by Mitutoyo



COOLANT PROOF™ IP67

COOLANT PROOF is the universal term of Mitutoyo Digimatic Small Tool Instruments that are free from measurement error and physical deterioration due to routine exposure to water, cutting oil or coolant. This high performance is achieved by using encoders that are inherently immune to contamination, where exposure is inevitable, combined with comprehensive sealing techniques and extremely oil-resistant materials to guarantee a long working life under normal operating conditions.

Digimatic Carbon Fiber Caliper



552-314-10

IP66 SPC ABSOLUTE

MeasurLink ENABLED Data Management Software by Mitutoyo


Order No.	Range	Accuracy	Resolution	List	Promo
552-312-10	0(.5")*-18"	+/-.002"	.0005"/0.01mm	$1,483.00	$1,424.00
552-313-10	0(.5")*-24"	+/-.002"	.0005"/0.01mm	$1,678.00	$1,611.00
552-314-10	0(1")*-40"	+/-.002"	.0005"/0.01mm	$2,991.00	$2,871.00
552-315-10	0(1")*-60"	+/-.004"	.0005"/0.01mm	$3,575.00	$3,432.00
552-316-10	0(1")*-80"	+/-.005"	.0005"/0.01mm	$5,593.00	$5,369.00

In parentheses = ID smallest range SPC cable – 1m: **05CZA624** 2m: **05CZA625**

- Lightweight Digimatic Calipers that employ CFRP (Carbon Fiber Reinforced Plastics) in the beam and jaws.
- Highly durable and easy to handle.
- Direct readout of ID measurements from the LCD. (Offset value can be set easily by pressing the Offset key.)
- Preset function for setting a desired starting point.
- With SPC data output.
- Special models available with ceramic jaws which are suitable for measuring abrasive and magnetic products.
- Can be used in workshop conditions exposed to coolant, water, dust or oil.
- Incorporates ABSOLUTE measurement system.
- Automatic power On/Off.



CERA Caliper Checker



20% OFF

Order No.	Range	Remarks (length to check)	List	Promo
515-565	0 - 12"	Outside measurement: 1", 2", 4", 6", 8", 10", 12" Inside measurement: 1", 2", 4", 6", 8", 10", 12"	$6,931.00	$5,545.00

CERA Caliper Checker

- Permanently wrung, high grade CERA gage blocks in a protective metal casing.
- Stands perpendicular for height gage inspection.

* Also includes same features as CERA Gage Blocks

CERA (Zirconia Ceramic) Gage Blocks*

- Extremely high wear resistance, 3x better than carbide.
- Corrosion proof – no oil needed.
- Closest expansion coefficient to steel.
- Anti-magnetic – keeps away steel dust.
- High wringing force due to high density.
- Crack and burr resistant.
- Low thermal conductivity – excellent dimensional stability under brief temperature changes (from handling, etc.).

QuantuMike

High-speed, high-accuracy micrometer measures 4x faster vs standard micrometers

NEW Products

SCAN ME

20% OFF

DIGIMATIC S1

IP65



4x Faster
1µm Accuracy



New Features

- Go/No-go icons: at-a-glance verification
- Calibration date alerts: warning and due date alerts
- Approach Speed Warning: reduce over-torquing
- Calculation: auto-calculate corrections and more
- S1 Digimatic output — send measurement to Excel or easily program features with software (ITPak 3.0 or MeasurLink®)
- Auto power On/Off. Key customization

GO/NG icons

Displays tolerance judgment mark

Tolerance judgment function: ON

Pass



Auto-calculate

Calculates and displays correction value

Calculation function: ON

Correction value can be read directly



Customized key setting allows the user to easily switch between measurement values and calculation results with the press of a button.

Calibration alerts

Forewarning

Calendar icon flashes



Due date

Entire display flashes



Continued Great Features

- 4x faster spindle speed
- Preset, Zero, Hold, Function Lock, Error display
- 1-pc Rachet Thimble + Speeder
- Resolution: .00005" / 0.001mm
- Accuracy: +/- .00005" / 0.001mm

Order No.	Description	List	Promo
293-180-40	QUANTUMIKE MICROMETER, DIGIMATIC, 0-1", IP65, .00005", W/SPC	$435.00	$348.00
293-181-40	QUANTUMIKE MICROMETER, DIGIMATIC, 1-2", IP65, .00005", W/SPC	$497.00	$398.00
293-182-40	QUANTUMIKE MICROMETER, DIGIMATIC, 2-3", IP65, .00005", W/SPC	$592.00	$474.00
293-183-40	QUANTUMIKE MICROMETER, DIGIMATIC, 3-4", IP65, .00005", W/SPC	$638.00	$510.00

QuickMikes

The updated QuickMike series still boasts the super-fast spindle feed rate that's **20x faster** than standard micrometers.

- IP65 protection – can be used around cutting fluids.
- MIN Hold – the minimum measurement can be held on the display for more repeatable and accurate measurements.
- Larger LCD – 33% larger, 10mm character height.
- Function lock – prevents accidental changes.
- 5 year battery life – more operating time, less downtime looking for and replacing batteries.
- Non-rotating spindle.



293-676-20

ABSOLUTE™ SPC

MeasurLink® ENABLED
Data Management Software by Mitutoyo

COOLANT PROOF™ IP65

Order No.	Range	Resolution	Accuracy	Flatness	Parallelism	List	Promo
293-676-22	0 - 1.2"	.00005"/0.001mm	±0.0001"	0.000012"	0.00008"	$936.00	$889.00
293-677-22	1 - 2.2"	.00005"/0.001mm	±0.0001"	0.000012"	0.00008"	$1,021.00	$970.00

Order Numbers are subject to change, e.g. **500-196-30** will change to **500-196-32**

SPC cable with data switch – 1m: **05CZA662** 2m: **05CZA663**



Effective September 21 through December 18

MDH Micrometer - world's first 5µinch/0.1µm resolution micrometer

Using precision digital measuring tools together with a USB input tool improves both measurement results and data reliability. The high-accuracy MDH with 5 millionths resolution can output in its entirety in both inch and metric. Resulting data can input directly to Excel®, MeasurLink® or other SPC programs.

› Range: 0-1", Resolution: .000005", Accuracy: +/- .000020

Order No.	Description	List	Promo
293-130-20	MDH Micrometer with high accuracy, high resolution output	$2,566.00	$2,309.00
Add-on Accessories			
05CZA662	SPC CONNECTING CABLE (1M)	$175.00	$158.00
264-020	USB INPUT TOOL	$303.00	$273.00



293-130-20



05CZA662



264-020

Package

MeasurLink® ENABLED
Data Management Software by Mitutoyo

MDC-Lite Micrometer

› Provided with zero set and in/mm (inch/metric models only) keys.
› A ratchet stop or friction thimble for a constant measuring force.
› Measurement readout with large characters on the LCD.
› No spindle clamp. No data output.

Order No.	Range	Resolution	Remarks	List	Promo
293-831-32	0 - 1" / 0 - 25.4mm	.00005" / 0.001mm	Ratchet Stop	$238.00	$226.00
293-832-32	0 - 1" / 0 - 25.4mm	.00005" / 0.001mm	Friction Thimble	$253.00	$240.00

Order Numbers are subject to change, e.g. **500-196-30** will change to **500-196-32**



293-831-30

Digimatic Micrometer

› New electromagnetic ABSOLUTE sensor - Improved resistance to environmental conditions such as dirt, oil and water, which can cause false readings.
› New ratchet thimble on select models improves one-hand operability.
› New anti-slip finish for improved grip while taking measurements.
› Long battery life – 2.4 years under normal operation.
› Fully compatible with existing Mitutoyo Digimatic peripherals (SPC cables, U-WAVE wireless transmitters, DP1-VA, etc.) – SPC output-enabled IP65 models.
› Function-lock system prevents inadvertent setting changes.
› Certificate of Inspection provided.



293-330-30

IP65

SPC

COOLANT PROOF™

	Order No.	Range	Resolution	Remarks	List	Promo
fit	293-330-32*	0-1"/0-25.4mm	.00005"/0.001mm	Ratchet Stop	$378.00	$359.00
	293-340-32	0-1"/0-25.4mm	.00005"/0.001mm	Ratchet Stop	$348.00	$331.00
	293-344-32	0-1"/0-25.4mm	.00005"/0.001mm	Ratchet Thimble	$370.00	$352.00
	293-348-32	0-1"/0-25.4mm	.00005"/0.001mm	Friction Thimble	$370.00	$352.00
	293-349-32	0-1"/0-25.4mm	.0001"/0.001mm	Ratchet Thimble, Tenths Reading	$316.00	$300.00
fit	293-331-32*	1-2"/25.4-50.8mm	.00005"/0.001mm	Ratchet Stop w/Standard	$445.00	$423.00
	293-341-32	1-2"/25.4-50.8mm	.00005"/0.001mm	Ratchet Stop w/Standard	$400.00	$380.00
	293-345-32	1-2"/25.4-50.8mm	.00005"/0.001mm	Ratchet Thimble w/Standard	$383.00	$364.00
fit	293-334-32*	0-1"/0-25.4mm	.00005"/ 0.001mm	Ratchet Thimble	$406.00	$386.00
fit	293-335-32*	0-1"/0-25.4mm	.00005"/0.001mm	Friction Thimble	$420.00	$399.00

*with SPC Output fit U-WAVE Fit compatible SPC cable with data switch – 1m: **05CZA662** 2m: **05CZA663**

Order Numbers are subject to change, e.g. **500-196-30** will change to **500-196-32**

MeasurLink® ENABLED
Data Management Software by Mitutoyo



Soft Case Tool Kits

Durable Protective Cases

New protective cases for your tools offer a modern alternative to our wooden cases. Versions include mechanical, standard Digimatic, or QuantuMike-based sets. QuantuMikes are just as accurate as standard Digimatic micrometers, but up to 4x faster.

Empty cases are also available as a new home for your existing tools!

NEW Products



64PKA288A





RUGGED, IMPACT-RESISTANT BUILD

CASE MOULDS FOR DIGIMATIC AND MECHANICAL TOOLS

LONG-LIFE ZIPPERS AND STAIN-RESISTANT COVER

2X MAGNET-BACKED SLOTS FOR HOLDING STEEL RULES, SPANNERS, THUMB DRIVES AND MORE



Effective September 21 through December 18



64PKA283

Soft Case Tool Kit Components for 64PKA283

Order No.	Description
103-135	MIC, OUTSIDE, 0-1", 0.0001", FRICTION THIMBLE
182-204	STEL RULE 6'' 3R FLEXIBLE
505-742J	DIAL CALIPER, 6'', .1"/ REV
64PMT183	CASE FOR MECHANICAL TOOL KIT



64PKA284

Soft Case Tool Kit Components for 64PKA284

Order No.	Description
103-177	MIC, OUTSIDE, 0-1", 0.001", RATCHET STOP
182-102	STEL RULE 6'' 16R RIGID
505-740J	DIAL CALIPER, 6'', .2"/ REV
64PMT183	CASE FOR MECHANICAL TOOL KIT



64PKA285B

Soft Case Tool Kit Components for 64PKA285B

Order No.	Description
293-340-32	1" RATCHET STOP MICROMETER (NO SPC)
500-196-32	DIGIMATIC CALIPER, 6"/150MM, NO OUTPUT
64PMT182	CASE FOR DIGIMATIC TOOL KIT



64PKA286B

Soft Case Tool Kit Components for 64PKA286B

Order No.	Description
293-348-32	1" FRICTION THIMBLE MICROMETER (NO SPC)
500-196-32	DIGIMATIC CALIPER, 6"/150MM, NO OUTPUT
64PMT182	CASE FOR DIGIMATIC TOOL KIT



64PKA288A

Soft Case Tool Kit Components for 64PKA288A

Order No.	Description
293-180-40	QUANTUMIKE MICROMETER, DIGIMATIC, 0-1", IP65, .00005", W/ SPC
500-171-30	DIGIMATIC CALIPER, 6"/150MM, W/ OUTPUT
64PMT182	CASE FOR DIGIMATIC TOOL KIT

Soft Case Tool Packages

Order No.	Description	List	Promo
64PKA283	TOOL PKG, MECHANICAL, INCH, W/ 6" DIAL CALIPER, 1" OUTSIDE MIC, 6" STEEL RULE, CASE	$505.00	$480.00
64PKA284	TOOL PKG, MECHANICAL, INCH, W/ 6" DIAL CALIPER, 1" MIC, 6" STEEL RULE, CASE	$475.00	$451.00
64PKA285B	TOOL PKG, DIGIMATIC, INCH, W/ 1" MIC (RATCHET STOP TYPE), 6" CALIPER, CASE	$654.00	$621.00
64PKA286B	TOOL PKG, DIGIMATIC, INCH, W/ 1" MIC (FRICTION THIMBLE TYPE), 6" CALIPER, CASE	$697.00	$662.00
64PKA288A	TOOL PKG, DIGIMATIC, INCH, W/1" QUANTUMIKE, 6" CALIPER, CASE, WITH OUTPUT	$817.00	$776.00

Order Numbers are subject to change, e.g. **500-196-30** will change to **500-196-32**

Protective Case Only

Order No.	Description	List	Promo
64PMT182	CASE FOR DIGIMATIC TOOL KIT	$94.00	$89.00
64PMT183	CASE FOR MECHANICAL TOOL KIT	$97.00	$92.00



Power grip model also available for even easier positioning.

High-Accuracy Linear Height Gage LH-600F/FG

The highest accuracy Linear Height Gage on the market is now even easier to use.

The Mitutoyo LH-600F Linear Height Measurement System is the latest model in the Mitutoyo Linear Height Gage line, designed to be more user-friendly while maintaining the best-in-class reliability and accuracy of previous models.


New Features:

- Rotatable, adjustable touch screen interface.
- New self-check feature.
- High-accuracy encoder more resistant to contaminants.
- Improved 2D mode.
- Calibration date warning.
- S1 Digimatic output capable of sending data directly to Excel®, wired or wirelessly.
- Additional probe and extension options.


Still Featuring:

- Resolution down to 0.1µinch (selectable).
- Highest accuracy in its class ± (1.1+0.6L/600) µm.
- Pneumatic full/semi-float system with built-in compressor.
- Capable of standard measurements such as heights and diameters or advanced measurements like angles, diagonal distances and perpendicularity (optional probes may be required).
- The Origin can be set at centerline positions, peaks of radii or simply on the surface plate or gage blocks.


Perpendicular/straightness measurement - Graph creation



Show results in real time during measurement.



Show results after measurement.



You can monitor the graphs of past measurement results.



Show measurement results in graph form.

Order No.	Description	Range (Stroke)	Resolution (selectable)	Package List	Promo
518-360-13	HEIGHT,LINEAR, LH-600F INCH/MM, S-518 (02ZAA010 Power Cord Not Included)	977mm (600mm) / 38" (24")	0.0001/0.001/0.01/0.1mm .0000001/.000001/.00001/.0001"	$13,861.00	**$13,168.00**
518-361-13	HEIGHT, LINEAR, 24", LH-600FG (02ZAA010 Power Cord Not Included)			$14,591.00	**$13,861.00**

*Must purchase Power Cord 02ZAA010

Effective September 21 through December 18



64PKA129D

ABSOLUTE 1D Height Gage QM-Height Series

- High-resolution ABSOLUTE linear encoder for position detection.
- High-accuracy: ±(2.4 + 2.1L / 600)µm.
- Pneumatic flotation system / positioning grip allows for smooth movement along surface plate (select models).
- Large, stationary display panel with user-friendly icon control keys and Go/No-go LED indicator.
- Digital and USB output: Supports Mitutoyo wireless SPC output.
- Fully compatible with existing Mitutoyo Digimatic peripherals (SPC cables, U-WAVE wireless transmitters, multiplexers, etc.).
- Battery life of 1200 hours in continuous use with four AA batteries, an improvement from 300 hours.

GO/±NG judgment by LED (red, orange, green) and measurement examples



d2 Digimatic and USB outputs



To install **U-WAVE-T**, separately purchase the optional mounting plate (**02AZE990**).



Order No.	Range	Resolution	Remarks	List	Promo
64PKA094D	0 - 14"/ 0 - 350mm	0.001mm / 0.0005mm /.00005" / .0001" (selectable)		$6,892.00	$6547.00
64PKA095D	0 - 24"/ 0 - 600mm			$7,743.00	$7356.00
64PKA129D	0 - 14"/ 0 - 350mm		Pneumatic Flotation System	$9,164.00	$8,706.00
64PKA130D	0 - 24"/ 0 - 600mm			$8,478.00	$8,054.00

ABSOLUTE Digimatic Height Gages

Popular Mitutoyo single-beam height gages have been redesigned to be even easier to use with larger displays, various hardware accessories, and multiple data options such as wired and wireless output, data loggers and more.

Features:

- Durable Build - Iron detector and base, steel beam and holder.
- Easy to use slider feed wheel.
- Multiple data equipment options.
- Other improvements: twist-off battery cap, 20% larger LCD, handy Data button.

MeasurLink® ENABLED
Data Management Software by Mitutoyo

SPC



570-412



Shown with optional Test Indicator and mounting hardware (see page 9).




Shown with optional U-Wave Bluetooth® transmitter (see page 21 and connector 02AZD790F)

Order No.	Range	Resolution	Functions	Drive Method	Data Output	Max. response speed	Battery Life	List	Promo
570-412	0"-12"/0mm-300mm	0.0005" / 0/01mm	On/Off, Origin, Zero/ABS, Hold/ Data, inch/mm conversion"	Slider-feed Wheel (manual)	Digimatic d1	Unlimited	Approx. 5 Years Under Normal Use	$1,150.00	$1,035.00
570-413	0"-18"/0mm-450mm							$1,544.00	$1,390.00
570-414	0"-24"/0mm-600mm							$1,787.00	$1,608.00

Series Two Dial Indicators

- Improved impact, and oil-resistant materials are employed in the bezel. The improved shape of the crystal face helps with easier measurement readings.
- High-strength, heat-treated stainless steel spindles for longevity.
- Scratch, and chemical-resistant hard-coated crystals.
- Increased rigidity in the bearing plate for reducing the retracing error (20%), and 4-screw mounting for greater impact resistance.
- Inspection certificate included.
- No through screw-holes on the frame for high oil, and dust-resistance. The bezel clamp (optional) can be attached either to the right or left side.



Revolutionary stem-bushing design for trouble-free stem clamping (longer clamping range; maximum tightening torque at the clamping point with M5 screw: 150N•cm).



2803A-10



2424A-19

Order No.	Graduation	Range	Range/Rev	Type	Dial Reading	Accuracy First 2.5 Rev/Overall	Force	List	Promo
2358A-10*	.0001″	.5″	.01"	w/lug	0-10	.0001 / .0008	2.0N or less	$348.00	$331.00
2803A-10*	.0001″	.025″	.01"	w/lug	0-5-0	.0001 / .0001	2.5N or less	$253.00	$240.00
2416A-10*	.001″	1″	.1"	w/lug	0-100	.001 / .002	1.8N or less	$223.00	$212.00
2424A-19*	.001″	2″	1"	w/lug	0-100	.001 / .003	2.5N or less	$383.00	$364.00
2776A	.0005″	1″	.05"	w/lug	0-50	.0005 / .002	2.5N or less	$224.00	$213.00

*Jeweled bearing model


Bore Gages

- Carbide-tipped contact points for durability.
- The dial indicator is fully protected by a rugged cover.
- Optional extension rods can be attached for measuring deep holes.
- The grip minimizes the variation of measurements by reducing heat transfer from the operator's hand.



511-751-20

Order No.	Range	Graduation	Anvils	Spacers	List	Promo
With Indicator						
511-751-20	.7 - 1.4″	.0001″ (2923B-10)	9	2	$651.00	$618.00
511-752-20	1.4 - 2.5″		6	4	$632.00	$600.00
511-753-20	2.0 - 6.0″		11 (2" sub anvil)	4	$692.00	$657.00
511-754-20	4.0 - 6.5″		13	4	$913.00	$867.00
511-755-20	6.5 - 10″		6	7	$1,031.00	$979.00
511-756-20	10 - 16″		5 (3" sub anvil)	7	$1,228.00	$1,167.00
Without Indicator						
511-731	.7 - 1.4″	Indicator optional Protective Cover optional (21DZA000)	9	2	$413.00	$392.00
511-732	1.4 - 2.5″		6	4	$423.00	$402.00
511-733	2.0 - 6.0″		11 (2" sub anvil)	4	$457.00	$434.00
511-734	4.0 - 6.5″		13	4	$683.00	$649.00
511-735	6.5 - 10″		6	7	$801.00	$761.00
511-736	10 - 16″		5 (3" sub anvil)	7	$1,006.00	$956.00





See Digimatic indicators made specifically for bore gages (page 10).

Effective September 21 through December 18

Dial Test Indicators




513-404-10E
Standard

.000050" / 50µinch model now available!

- One-piece movement assembly for improved durability & impact resistance.
- Contact point length shown on dial face.
- Certificate of Inspection included.
- Shows results from both measuring directions.
- Resilient crystal with high resistance to glare, scratches and impact.


OrderNo.	Range	Graduations	Set Type	Face Color	List	Promo	Remarks
Standard							
513-407-10E	.008"	.00005"	Basic	White	$294.00	$279.00	Fine grads
513-407-10T	.008"	.00005"	Full	White	$345.00	$328.00	Fine grads
513-401-10E	.14mm	0.001mm	Basic	Yellow	$350.00	$333.00	
513-402-10E	.03"	.0005"	Basic	White	$204.00	$194.00	
513-402-10T	.03"	.0005"	Full	White	$243.00	$231.00	
513-403-10E	.008"	.0001"	Basic	White	$266.00	$253.00	
513-403-10T	.008"	.0001"	Full	White	$312.00	$296.00	
513-404-10E	0.8mm	0.01mm	Basic	Yellow	$208.00	$198.00	
513-404-10A	0.8mm	0.01mm	Plus	Yellow	$229.00	$218.00	
513-404-10T	0.8mm	0.01mm	Full	Yellow	$244.00	$232.00	
513-405-10E	0.2mm	0.002mm	Basic	Yellow	$231.00	$219.00	
513-405-10T	0.2mm	0.002mm	Full	Yellow	$303.00	$288.00	
513-406-10E	.03"/0.7mm	.0005"/0.01mm	Basic	White/Yellow	$241.00	$229.00	Dual dial
513-406-10T	.03"/0.7mm	.0005"/0.01mm	Full	White/Yellow	$266.00	$253.00	Dual dial
513-409-10E	0.2mm/.0076"	0.002mm/.0001"	Basic	Yellow/White	$310.00	$295.00	Dual dial
513-409-10T	0.2mm/.0076"	0.002mm/.0001"	Full	Yellow/White	$315.00	$299.00	Dual dial
513-412-10E	.03"	.0005"	Basic	White	$294.00	$279.00	
513-412-10T	.03"	.0005"	Full	White	$339.00	$322.00	
513-415-10E	1.0mm	0.01mm	Basic	Yellow	$221.00	$210.00	Long stylus
513-415-10H	1.0mm	0.01mm	Basic	Yellow	$242.00	$230.00	Long stylus
Ruby Tip							
513-472-10E	.03"	.0005"	Basic	White	$229.00	$218.00	
513-479-10E	.03"	.0005"	Basic	White	$242.00	$230.00	Long stylus
Standard (20° tilted face)							
513-442-10A	.06"	.0005"	Basic	White	$278.00	$264.00	
513-442-10T	.06"	.0005"	Full	White	$315.00	$299.00	
513-442-16A	.06"	.0005"	Basic	Black	$278.00	$264.00	
513-442-16T	.06"	.0005"	Full	Black	$315.00	$299.00	
513-446-16A	.06"	.0005"	Basic	Black	$372.00	$353.70	Long stylus
513-446-16T	.06"	.0005"	Full	Black	$418.00	$397.00	Long stylus
513-446-10A	.06"	.0005"	Basic	White	$372.00	$353.00	Long stylus
513-446-10T	.06"	.0005"	Full	White	$418.00	$397.00	Long stylus
513-443-10A	.016"	.0001"	Basic	White	$350.00	$333.00	
513-443-10T	.016"	.0001"	Full	White	$396.00	$376.00	
Vertical: dial is on the top of the frame							
513-452-10E	.03"	.0005"	Basic	White	$266.00	$253.00	
513-452-10T	.03"	.0005"	Full	White	$294.00	$279.00	
513-453-10E	.008"	.0001"	Basic	White	$317.00	$301.00	
Parallel: dial is on the side of the frame							
513-485-10E	0.2mm	0.002mm	Basic	Yellow	$339.00	$322.00	




Contact point length is printed on dial face to avoid accuracy issues

Set Configuration

Inch



Metric




ID-C / ID-F Digimatic Indicators

High-performance ABS Digimatic Indicators

- 20 µinch/0.5 µm resolution.
- Large screen and analog bar.
- **Calibration period notification function.** The LCD displays an icon to notify the user when the set calibration time approaches. This facilitates the proper precision management of ID-C/ID-F.

Calibration period notification function



- Simple Calculation Function.
- **New Digimatic S1 Output*.** S1 is the new Mitutoyo bidirectional output format that enables reading and writing information to the gages such as sending a zero command, TIR reset, calibration date warnings, and the ability to poll the serial number for smoother measurement operation. Communication is supported by the new Input Tool and SPC cable, see table below.

Order No.	Description	List
06AGL011	SPC DIGIMATIC Cable, TYPE S1 (1M)	$142.00
264-020	USB INPUT TOOL	$303.00

* SPC Cable and Input Tool are both required



06AGL011

264-020

Excel®
Send data directly into existing forms

ITPak 3.0 Freeware
Read/Write Data and set Parameters

MeasurLink® 10.4 (see page 29)
Data Management & SPC Software

NEW Products

0.5" ID-F MODEL NOW AVAILABLE




ID-C Series



ID-F Series

Large screen and analog bar

The units have large screens that can display various information in an easy-to-read manner. They also have an analog bar, convenient for observing subtle movements such as the approach to tolerance.



ID-C Series - Battery Operated

Order No.		Range	Resolution	Maximum Permissible Error			Measuring for MPL (N)	Interface	Net mass (g)		List	Promo
With Lug	Flat Back			MPE_E	Hysteresis MPE_H	Repeatability MPE_R			With Lug	Flat Back		
543-702B	543-702B-02	0.5" / 12.7mm	0.00002" / .00005" / 0.0001" / 0.0005" / 0.0005mm / 0.001mm / 0.01mm	± 0.00012" / 0.002mm	0.00008" / 0.002mm	0.00008" / 0.002mm	1.5 or less	d1/d2/S1	195	165	$609.00	$579.00
543-707-02	543-707B-02	0.5" / 12.7mm					0.4 to 0.7	d1/d2/S1	190	160	$1,047.00	$995.00
-	543-722B-02	1" / 25.4mm					1.8 or less	d1/d2/S1	-	195	$900.00	$855.00
-	543-732B-02	2" / 50.8mm		± 0.0002" / 0.005mm			2.3 or less	d1/d2/S1	-	260	$1,123.00	$1,067.00
543-712-02	543-712B-02	0.5" / 12.7mm	0.0005" / 0.01mm	± 0.001" / 0.02mm	0.001" / 0.02mm	0.0005" / 0.01mm	0.9 or less	d1/S1	190	160	$490.00	$466.00
543-717-02	543-717B-02	0.5" / 12.7mm					0.2 to 0.5	d1/S1	185	155	$785.00	$746.00
-	543-727B-02	1" / 25.4mm					1.8 or less	d1/S1	-	190	$719.00	$683.00
-	543-737B-02	2" / 50.8mm		± 0.0015" / 0.04mm			2.3 or less	d1/S1	-	245	$941.00	$894.00

Order Numbers are subject to change, e.g. **500-196-30** will change to **500-196-32**

ID-F Series - AC Powered - Green/Red Backlit Display

Order No.		Range	Resolution	Maximum Permissible Error			Measuring for MPL (N)	Interface	List	Promo
With Lug	Flat Back			MPE_E	Hysteresis MPE_H	Repeatability MPE_R				
543-856-A	543-856B-A	0.5" / 12.7mm	0.005mm / 0.001mm / 0.01 mm / 0.00002" / .00005" / 0.0001" / 0.0005"/ 0.001" (selectable)	± 0.0001" / 0.0025mm	0.00008" / 0.002mm	0.00008" / 0.002mm	1.5 or less	d1/d2/S1	$903.00	$858.00
-	543-852A	1" / 25.4mm					1.8 or less	d1/d2/S1	$1,053.00	$1,000.00
-	543-854A	2" / 50.8mm		± 0.00016" / 0.004mm			2.3 or less	d1/d2/S1	$1,195.00	$1,135.00
-	543-858A			± 0.00012" / 0.003mm			2.3 or less	d1/d2/S1	$1,216.00	$1,155.00

Effective September 21 through December 18

Digimatic Indicator ID-H

Remote Programming Capable

- This digital indicator offers excellent accuracy and functionality with an easy-to-read display. Take advantage of its high accuracy, backed up by 0.5µm / .00002" resolution, remote control functionality via a handheld controller (or an RS-232C interface) and easy runout measurements with the analog bar display.
- With RS-232C input/output
- The maximum, minimum or runout value can be displayed during measurement.
- Go/No-go judgment is performed by setting the upper and lower tolerances. If a judgment result is out of tolerance, the display backlighting changes from green to red, so tolerance judgment can be made at a glance.

21EZA099
Remote controller
(optional)





543-564A

SPC

MeasurLink® ENABLED
Data Management Software by Mitutoyo

Stem dia. 3/8" #4-48 UNF Thread

Order No.	Resolution	Range	Model	Accuracy	List	Promo
543-562	.00002", .00005", .0001", 0.0005mm, 0.001mm	1.2" / 30.4mm	ID-H530E	0.0015mm	$1,539.00	$1,462.00
543-564		2.4" / 60.9mm	ID-H560E	0.0025mm	$1,818.00	$1,727.00

SPC cable – 1m: **936937** 2m: **965014**

ABSOLUTE Digimatic Indicator ID-S

- Employing the ABSOLUTE linear encoder, the ID-S always displays the spindle ABSOLUTE Position from the origin at power-on. Also, unlimited response speed eliminates overspeed errors.
- Dust/water protection level: IP42 (IP53: 543-796B-10).
- SPC data output

SPC

ABSOLUTE®

MeasurLink® ENABLED
Data Management Software by Mitutoyo



543-783B-10

Order No.	Resolution	Range	Accuracy	Measuring force	Remarks	List	Promo
Stem dia. 3/8", #4-48 UNF Thread							
543-792-12	.00005"/0.001mm	.5" / 12.7mm	±.0001"	1.5N or less	w/ lug back	$444.00	$422.00
543-796-12	.00005"/0.001mm	.5" / 12.7mm	±.0001"	2.5N or less	w/ lug-back	$477.00	$453.00
543-793-12	.0001"/0.001mm	.5" / 12.7mm	±.0001"	1.5N or less	w/ lug back	$444.00	$422.00
543-783-12	.0005"/0.01mm	.5" / 12.7mm	±.0010"	1.5N or less	w/ lug-back	$280.00	$266.00
543-792B-12	.00005"/0.001mm	.5" / 12.7mm	±.0001"	1.5N or less	w/ flat back	$444.00	$422.00
543-796B-12	.00005"/0.001mm	.5" / 12.7mm	±.0001"	2.5N or less	w/ flat-back	$477.00	$453.00
543-793B-12	.00005"/0.001mm	.5" / 12.7mm	±.0001"	1.5N or less	w/ flat back	$444.00	$422.00

ABSOLUTE Digimatic Indicator ID-U

- Economical, slim digital indicator.
- Large LCD and simple key operation.
- Ideal for installation into measuring devices because of its compact design and long battery life.
- Employing the ABSOLUTE linear encoder, the ID-U always displays the spindle ABSOLUTE position from the origin at power-on. Also, unlimited response speed eliminates overspeed errors.
- Long stem for mounting.



575-123

SPC

ABSOLUTE®

MeasurLink® ENABLED
Data Management Software by Mitutoyo

Order No.	Resolution	Range	Model	Accuracy	Measuring force	List	Promo
575-123	.0005"/0.01mm	1" / 25.4mm	ID-U1025E	.0008"	1.8N or less	$308.00	$293.00

SPC cable – 1m: **905338** 2m: **905409**

Calculation-Type Digimatic Indicator ID-C

- Calculation-type Digimatic Indicator features both a key lock and parameter lock.
- Fast measurement frequency up to 50 per second.
- An analog bar provides easy-to-read values when scanning for Max, Min and TIR Values.
- The ABSOLUTE Digimatic indicator performs internal calculations using the formula Ax+B+Cx-1 (assuming spindle displacement as x), while the specified coefficients A, B and C can be set with respect to the purpose of measurement or dimensions of the fixtures. This unique feature allows for reading measurements directly without searching for conversions.
- Improved parameter setting software makes it even easier to set all of the available parameters to determine and upload the proper coefficients for calculation. (optional) **21EZA313**



Custom fixture shown

SPC ABSOLUTE®

MeasurLink® ENABLED
Data Management Software by Mitutoyo



543-342B-10

Order No.	Resolution	Range	Accuracy	Measuring Force	List	Promo
543-342B-10	.00005/.0001/.0005" (0.001/0.01mm) Selectable	.5"/12.7mm	±.00010"/0.003mm	1.5N or less	$700.00	$665.00

Stem dia. 3/8" #4-48 UNF Thread

SPC cable – 1m: **905338** 2m: **905409**



Installed on optional bore gage probe (page 12)

Bore Gage ABSOLUTE Digimatic Indicator ID-C

- Hold automatically picks up hole diameter after a sweep.
- Bore Gage Digimatic Indicator features both a key lock and parameter lock.
- Fast measurement frequency up to 50 per second.
- Analog bar provides easy-to-read values when scanning for Max, Min and TIR values.
- Up to three sets of master values and upper/lower tolerance values can be stored.
- Go/No-go judgment
- Employing the ABSOLUTE linear encoder, the ID-C always displays the spindle ABSOLUTE Position from the origin at power-on.
- Improved parameter setting software makes it even easier to set all of the available parameters to determine and upload the proper coefficients for calculation. (optional) **21EZA313**

MeasurLink® ENABLED
Data Management Software by Mitutoyo



543-312B-10

Order No.	Resolution	Range	Accuracy	Measuring Force	List	Promo
543-312B-10	.00005/.0001/.0005" (0.001/0.01mm) Selectable	.5"/12.7mm	±.00010"/0.003mm	1.5N or less	$700.00	$665.00

SPC ABSOLUTE®

SPC cable – 1m: **905338** 2m: **905409**

Peak Hold ABSOLUTE Digimatic Indicator ID-C

With Max./Min. Value Holding Function

- Peak Hold Digimatic Indicator features both a Key Lock and Parameter Lock.
- An analog bar provides easy-to-read values when scanning for Max, Min and TIR Values.
- Go/No-go judgment
- The maximum, minimum or runout value can be displayed during measurement.
- Fast measurement frequency up to 50 per second.
- Employing the ABSOLUTE linear encoder, the Signal ID-C always displays the spindle ABSOLUTE Position from the origin at power-on.
- Improved parameter setting software makes it even easier to set all of the available parameters and then determine and upload the proper coefficients for calculation. (optional) **21EZA313**



543-302B-10

Order No.	Resolution	Range	Accuracy	Remarks	List	Promo
Stem dia. 3/8", #4-48 UNF Thread						
543-302-10	.00005/.0001/.0005" 0.001/0.01mm Selectable	.5"/12.7mm	±.00010"/0.003mm	w/lug	$700.00	$665.00
543-302B-10		.5"/12.7mm	±.00010"/0.003mm	Flat-back	$700.00	$665.00

SPC ABSOLUTE®

MeasurLink® ENABLED
Data Management Software by Mitutoyo

SPC cable – 1m: **905338** 2m: **905409**

Effective September 21 through December 18

Boremetic

10% OFF

Quick, spring-loaded lever action/movement

- Titanium-coated measuring pins provide excellent durability and impact resistance while allowing the instrument to measure close to the bottom of blind holes.
- Digital display with quick-action lever operation enables quick and easy measurement.
- Built-in ABSOLUTE System eliminates the need to set the origin point every time the unit is turned on. The system is immune to over-speed errors, thus increasing the reliability of measurement.
- The Digimatic Boremetic is compatible with statistical process control systems and measurement support systems.
- Built-in tolerance judgment function allows Go/No-go judgment based on user-defined upper and lower limit settings.

MeasurLink® ENABLED Data Management Software by Mitutoyo

ABSOLUTE®

SPC



Individual Gages: includes one digital display unit and one interchangeable measuring head (plus adapter if required)

Order No.	Size Range	Accuracy	Extension Rod	List	Promo
568-461	0.275″ - 0.350″	±5µm ±0.00025 in	100mm (952322)	$2,043.00	$1,839.00
568-462	0.350″ - 0.425″			$2,247.00	$2,022.00
568-463	0.425″ - 0.500″			$2,225.00	$2,003.00
568-464	0.50″ - 0.65″	±5µm ±0.00025 in	150mm (952621)	$2,085.00	$1,877.00
568-465	0.65″ - 0.80″			$2,274.00	$2,047.00
568-466	0.8″ - 1.0″	±6µm ±0.0003 in	150mm (952622)	$2,274.00	$2,047.00
568-467	1.0″ - 1.2″			$2,156.00	$1,940.00
568-468	1.2″ - 1.6″			$2,590.00	$2,331.00
568-469	1.6″ - 2.0″			$2,590.00	$2,331.00
568-470	2.0″ - 2.5″		150mm (952623)	$2,541.00	$2,287.00
568-471	2.5″ - 3.0″			$2,423.00	$2,181.00
568-472	3.0″ - 3.5″			$2,675.00	$2,408.00
568-473	3.5″ - 4.0″			$2,465.00	$2,219.00
568-474	4.0″ - 4.5″			$2,578.00	$2,320.00
568-475	4.5″ - 5.0″			$2,719.00	$2,447.00

Technical Data

Resolution:	0.001mm or 0.00005in/0.001mm
Display:	LCD
Response speed:	Infinite
Battery:	SR44 (1 pc), **938882**, for initial operational checks (standard accessory)
Battery life:	Approx. 5,000 hours in continuous use
Scale type:	Electrostatic capacitance ABSOLUTE encoder

Functions

Go/No-go judgment, Go/No-go judgment zoom, 2-Point preset, Zero-setting, Data hold, Error alarm, Low battery voltage alert, Data output, Function lock, 330° Rotary display, inch/mm conversion (inch/mm models)

Complete Unit Gage Sets: includes several individual gages to cover the overall size range of the set

Order No.	Overall Range	Range of Individual Gages	Setting Rings	List	Promo
568-966	0.5″ - 1″	0.5-0.65″, 0.65-0.8″, 0.8-1″	0.65″ DIA., 0.8″ DIA.	$7,368.00	$6,631.00
568-967	1″ - 2″	1-1.2″, 1.2-1.6″, 1.6-2″	1.2″ DIA., 1.6″ DIA.	$7,692.00	$6,923.00
568-968	2″ - 3″	2-2.5″, 2.5-3″	2.5″ DIA.	$5,508.00	$4,957.00
568-969	3″ - 4″	3-3.5″, 3.5-4″	3.5″ DIA.	$6,651.00	$5,986.00
568-965-10	0.275″ - 0.5″	0.275-0.35″, 0.35-0.425″, 0.425-0.5″	0.35″ DIA., 0.425″ DIA.	$7,697.00	$6,927.00



Complete-Unit Set

Interchangeable-Head Sets

Order No.	Overall Range	Range of Individual Gages	Setting Rings	List	Promo
568-928	0.275″ - 0.5″	0.275-0.35″, 0.35-0.425″, 0.425-0.5″	0.35″ DIA., 0.425″ DIA.	$3,429.00	$3,086.00
568-929	0.5″ - 1″	0.5-0.65″, 0.65-0.8″, 0.8-1″	0.65″ DIA., 0.8″ DIA.	$3,564.00	$3,208.00
568-930	1″ - 2″	1-1.2″, 1.2-1.6″, 1.6-2″	1.2″ DIA., 1.6″ DIA.	$4,730.00	$4,257.00
568-936	2″ - 4″	2-2.5″, 2.5-3″, 3-3.5″, 3.5-4″	2.5″ DIA., 3.5″ DIA.	$6,254.00	$5,629.00



Interchangeable-Head Set

Includes one digital display unit with several interchangeable measuring heads (and adapters as required) to cover the total size range plus one extension rod
Order Numbers are subject to change, e.g. **500-196-30** will change to **500-196-32**

Digimatic Holtest

- Titanium-coated measuring pins provide excellent durability and impact resistance while allowing the instrument to measure close to the bottom of blind holes.
- Large LCD readout.
- Functions available: Presetting, Zero/ABS, Auto power On/Off, Data hold, Data output, Error alarm, Battery replacement alarm.
- With ratchet stop for consistent force.
- Measure deep holes by attaching an extension rod (optional).
- Setting rings are included in sets, but optional for individual gages.
- Supplied in fitted plastic case up to 4"/100mm. Over 4"/100mm supplied in wooden case.
- Resolution: .00005"/0.001mm (over 4" models: .0001"/0.001mm)



10% OFF

MeasurLink® ENABLED
Data Management Software by Mitutoyo


SPC IP65

Digimatic Holtests – Individual Units

Order No.	Range	List	Promo
468-261	Digimatic Holtest, .275 - .35"	$1,714.00	$1,543.00
468-262	Digimatic Holtest, .35" - .425"	$1,714.00	$1,543.00
468-263	Digimatic Holtest, .425 - .5"	$1,727.00	$1,554.00
468-264	Digimatic Holtest, 0.5" - 0.65"	$1,860.00	$1,674.00
468-265	Digimatic Holtest, 0.65" - 0.8"	$1,860.00	$1,674.00
468-266	Digimatic Holtest, 0.8" - 1"	$1,921.00	$1,729.00
468-267	Digimatic Holtest, 1.0 - 1.2"	$1,921.00	$1,729.00
468-268	Digimatic Holtest, 1.2" - 1.6"	$1,970.00	$1,773.00
468-269	Digimatic Holtest, 1.6" - 2.0"	$1,982.00	$1,784.00
468-270	Digimatic Holtest, 2" - 2.5"	$2,152.00	$1,937.00
468-271	Digimatic Holtest, 2.5" - 3"	$2,152.00	$1,937.00
468-272	Digimatic Holtest, 3" - 3.5"	$2,176.00	$1,958.00
468-273	Digimatic Holtest, 3.5" - 4"	$2,213.00	$1,992.00
468-274	Digimatic Holtest, 4" - 5"	$2,882.00	$2,594.00
468-275	Digimatic Holtest, 5" - 6"	$2,967.00	$2,670.00
468-276	Digimatic Holtest, 6" - 7"	$3,149.00	$2,834.00
468-277	Digimatic Holtest, 7" - 8"	$3,259.00	$2,933.00
468-278	Digimatic Holtest, 8" - 9"	$3,502.00	$3,152.00
468-279	Digimatic Holtest, 9" - 10"	$3,575.00	$3,218.00
468-280	Digimatic Holtest, 10" - 11"	$3,708.00	$3,337.00
468-281	Digimatic Holtest, 11" - 12"	$3,854.00	$3,469.00

Measuring Deep Holes

An extension rod (optional accessory) can be fitted to provide measurement of deep holes.



Digimatic Holtests – Interchangeable Head Sets

Order No.	Range	List	Promo
468-976	Digimatic Holtest Head Set, 0.275" - 0.5"*	$3,113.00	$2,802.00
468-977	Digimatic Holtest, Head Set, 0.5" - 0.8"*	$2,529.00	$2,276.00
468-978	Digimatic Holtest, Head Set, 0.8" - 2"*	$6,311.00	$5,680.00
468-979	Digimatic Holtest, Head Set, 2" - 4"*	$7,235.00	$6,512.00
468-980	Digimatic Holtest, Head Set, 4" - 8"*	$8,499.00	$7,649.00

Digimatic Holtests – Complete Unit Sets

Order No.	Range	List	Promo
468-986	Digimatic Holtest, Unit-Set, 0.275" - 0.5"*	$6,055.00	$5,450.00
468-987	Digimatic Holtest, Unit-Set, 0.5" - 1"*	$6,444.00	$5,800.00
468-988	Digimatic Holtest, Unit-Set, 1" - 2"*	$7,308.00	$6,577.00
468-989	Digimatic Holtest, Unit-Set, 2" - 3"*	$8,195.00	$7,376.00
468-990	Digimatic Holtest, Unit-Set, 3" - 4"*	$9,642.00	$8,678.00



Complete-Unit Set




Interchangeable-Head Set

Effective September 21 through December 18

Holtest

- Titanium-coated measuring pins provide excellent durability and impact resistance while allowing the instrument to measure close to the bottom of blind holes.
- Three-point design ensures self-centering action for stable measurements in the range above .275" bore diameter.
- With ratchet stop for consistent force.



Two-point contact type

Holtest Type II

- Holtest Type II models are also available. These lower-costs units have solid, hardened alloy steel anvils.


Mechanical Holtests – Individual Units

Order No.	Description/Range	List	Promo
368-021	Holtest, 0.08" - 0.1"	$2,310.00	$2,079.00
368-022	Holtest, 0.1" - 0.12"	$2,310.00	$2,079.00
368-023	Holtest, 0.12" - 0.16"	$1,848.00	$1,663.00
368-024	Holtest, 0.16" - 0.2"	$1,848.00	$1,663.00
368-025	Holtest, 0.2" - 0.24"	$1,848.00	$1,663.00
368-026	Holtest, 0.24" - 0.28"	$1,848.00	$1,663.00
368-261	Holtest, 0.275" - 0.35"	$918.00	$826.00
368-262	Holtest, 0.35" - 0.425"	$918.00	$826.00
368-263	Holtest, 0.425" - 0.5"	$918.00	$826.00
368-264	Holtest, 0.5" - 0.65"	$952.00	$857.00
368-265	Holtest, 0.65" - 0.8"	$952.00	$857.00
368-266	Holtest, 0.8" - 1.0"	$989.00	$890.00
368-267	Holtest, 1.0" - 1.2"	$989.00	$890.00
368-268	Holtest, 1.2" - 1.6"	$1,240.00	$1,116.00
368-269	Holtest, 1.6" - 2.0"	$1,301.00	$1,171.00
368-270	Holtest, 2.0" - 2.5"	$1,313.00	$1,182.00
368-271	Holtest, 2.5" - 3.0"	$1,423.00	$1,281.00
368-272	Holtest, 3.0" - 3.5"	$1,459.00	$1,313.00
368-273	Holtest, 3.5" - 4.0"	$1,520.00	$1,368.00
368-274	Holtest, 4.0" - 5.0"	$1,970.00	$1,773.00
368-275	Holtest, 5.0" - 6.0"	$2,225.00	$2,003.00
368-276	Holtest, 6.0" - 7.0"	$2,286.00	$2,057.00
368-277	Holtest, 7.0" - 8.0"	$2,371.00	$2,134.00
368-278	Holtest, 8.0" - 9.0"	$2,675.00	$2,408.00
368-279	Holtest, 9.0" - 10"	$3,015.00	$2,714.00
368-280	Holtest, 10" - 11"	$3,040.00	$2,736.00
368-281	Holtest, 11" - 12"	$3,113.00	$2,802.00

Mechanical Holtests – Complete Unit Sets

Order No.	Description/Range	List	Promo
368-916	Holtest, Set, 0.275" - 0.5"*	$3,392.00	$3,053.00
368-917	Holtest, Set, 0.5" - 0.8"*	$2,286.00	$2,057.00
368-918	Holtest, Set, 0.8" - 2.0"*	$5,228.00	$4,705.00
368-919	Holtest, Set, 2.0" - 4.0"*	$7,441.00	$6,697.00
368-920	Holtest, Set, 4.0" - 8.0"*	$11,405.00	$10,265.00
368-926	Holtest, 2pc Set, .08" - .12"*	$4,900.00	$4,410.00
368-927	Holtest, 4pc Set, .12" - .28"*	$7,794.00	$7,015.00

10% OFF




Measuring Deep Holes

An extension tube (optional accessory) can be fitted to enable measurement of deep holes.

Measuring a Blind Hole

The measuring contact points held in the jaws permit measuring the diameter of a blind hole to the bottom.
(up to 100mm / 4" models)




Range	a	b	c
6 - 12mm / .275 - .5"	2	—	2.5
12 - 20mm / .5 - .8"	0.3	5.6	3.5
20 - 30mm / .8 - 1.2"	0.3	8.3	5.2
30 - 50mm / 1.2 - 2"	0.3	13	10
50 - 100mm / 2 - 4"	0.3	17	14
100 - 300mm / 4 - 12"	12.4	21	13.8



TiN coated contact points

Inspection Certificate Supplied as Standard

An Inspection Certificate is supplied with each instrument, which assures product quality and safety. On request, Mitutoyo can issue a Calibration Certificate, at a cost, from our accredited calibration laboratory.



U-WAVE is a wireless system that turns any Mitutoyo gage with Digimatic output into a wireless keyboard for fast, error-free data collection. U-WAVE transmitters now come in three models: Bluetooth®, Fit and Standard. Send data with a push of a button or request it from the PC or mobile device.

Bluetooth™

U-WAVE Bluetooth®

NEW Products


Request an assessment to determine how quickly your company can obtain a full ROI




U-WAVE-TMB/TCB

The new U-WAVE Bluetooth® transmitter features:

- Now utilizes the popular Bluetooth® 4.2 Low Energy Wireless Technology.
- This new Bluetooth® version of U-WAVE allows a simple connection to smartphones, tablets and Bluetooth® enabled Laptops and PC's.
- The same low-profile and ergonomic fit benefits of the U-WAVE-Fit.
- A buzzer type and IP67 type with dustproof and waterproof specifications are available.
- Up to 7 units can be connected to 1 Bluetooth® enabled PC without a receiver.
- New U-WAVEPak for Android, iOS and Windows available at no cost.





GET IT ON Google Play Download on the App Store

The Google Play and Google Play logos are trademarks of Google LLC.
The Apple and Apple logos are trademarks of Apple Inc.

The measurement data is used to make the software in the pc Transferable PC Communication Software U-WAVEPAK-BW.

IP67

U-WAVE-TMB



MeasurLink® ENABLED
Data Management Software by Mitutoyo

10% OFF

U-WAVE-TCB



U-WAVE-TMB/TCB*

Order No.	Model	Measuring Instrument*	Remarks	List	Promo
264-624-IP-S	U-WAVE-TCB	4", 6", 8", 12" standard caliper	Transmitter and Connection Unit	$414.00	$373.00
264-624-IP	U-WAVE-TCB	4", 6", 8", 12" IP67 caliper	Transmitter and Connection Unit	$414.00	$373.00
264-626-IP-M	U-WAVE-TMB	Coolant-proof (IP65) micrometer Micrometers (excl. S1, excl. QuickMike)	Transmitter and Connection Unit	$414.00	$373.00
02AZF700-TMB	U-WAVE-TMB	0.5" (12.5mm) Stroke for S1 Indicators	Transmitter and Connection Unit	$429.00	$386.00
02AZG011-TMB	U-WAVE-TMB	1" (25.4mm) Stroke or Larger for S1 Indicators	Transmitter, Bracket, and Connection Unit	$521.00	$469.00

* No U-WAVE Receiver required

Effective September 21 through December 18

U-WAVE Wireless Data Transmitters

All prices are in Canadian Dollars

UP TO 10% OFF

U-WAVE fit

The new Mitutoyo U-WAVE-Fit wireless data transmitter fits to the back of popular Mitutoyo hand-held measuring instruments. This new design allows for a snug fit behind the display resulting in a more ergonomic feel. U-WAVE-Fit is the same technology as the U-WAVE-T, just a smaller version.

For micrometers
U-WAVE-TM





For calipers
U-WAVE-TC





U-WAVE-TM for micrometers and U-WAVE-TC for calipers are available both as the buzzer and water/dust-proof IP67 types. The buzzer type notifies the normal reception of data by LED and buzzer sound. The water/dust-proof IP67 type is designed for harsh environments and therefore is only equipped with LED notification of data reception.

MeasurLink® ENABLED
Data Management Software by Mitutoyo

- The transmitter is designed to fit in the space behind the display, and the connecting cable has been replaced by a rigid connector.
- Approx. 20 m transmission range (within visible range).
- 2.4GHz wireless system for reliable and secure data transmission.
- Easy data export to Microsoft® Excel® or SPC software applications.
- Transmitter confirms data transfer by an LED signal and optional buzzer.
- An IP67 transmitter is available to ensure a coolant-proof gaging system.
- Low power consumption: 400,000 data transmissions with a single battery.

U-WAVE-Fit (Transmitter)

Order No.	Model	Measuring Instrument*	Remarks	List	Promo
264-620-IP-S	U-WAVE-TC	4", 6", 8", 12" IP67 standard caliper	Transmitter and Connection Unit	$459.00	$413.00
264-620-IP	U-WAVE-TC	4", 6", 8", 12" IP67 caliper	Transmitter and Connection Unit	$459.00	$413.00
264-622-IP-M	U-WAVE-TM	Coolant-proof (IP65) micrometer Micrometers (excl. S1, excl. QuickMike)	Transmitter and Connection Unit	$459.00	$413.00
02AZF700-TM	U-WAVE-TM	0.5" (12.5mm) Stroke for S1 Indicators	Transmitter and Connection Unit	$474.00	$427.00
02AZG011-TM	U-WAVE-TM	1" (25.4mm) Stroke or Larger for S1 Indicators	Transmitter, Bracket, and Connection Unit	$566.00	$509.00

* Please contact Mitutoyo or distributor for further details

U-WAVE-R (Receiver)

Order No.	Remarks	Software	Number of U-WAVE-R units that can be connected to PC	Number of U-WAVE-T units that can be connected	List	Promo
02AZD810D	U-WAVE-R + Software	U-WAVE PAK	Up to 15	Up to 100	$764.00	$688.00

PH-3515F Profile Projector and 2D Processor Packages

Heavy-Duty, Bench-Top Model with Horizontal Optical System featuring display w/ M2 geometric measuring software.

- ø14" screen, Horizontal Projector
- 10" x 6" Travel T Slot table for accessories
- Linear Glass Scales for accurate measurement
- Profile and Fiber Optic Surface Illumination
- Digital built-in angle counter
- Maximum Load 45kg / 100lb
- Available with M2 or QM Data 2D Processors

Order No.	Description	List	Promo
PH-3515 Main Unit & Digital Readout Packages 5% Off			
M172868-11	PH-3515F Profile Projector with KA counter & Tray	$18,426.00	$17,505.00
M172868-21	PH-3515F Profile Projector with QM Data & Arm Mount	$22,939.00	$21,792.00
M172868-41	PH-3515F Profile Projector with Touchscreen PC & M2 Software/Hardware	$22,251.00	$21,138.00
M172868-31	PH-3515F Profile Projector with QM Data, Arm Mount & Optoeye Edge Detection	$26,508.00	$25,183.00
M172868-51	PH-3515F Profile Projector with Optical Edge Detection, Touchscreen PC & M2 Software/Hardware	$24,318.00	$23,102.00
Machine Stand (Optional)		List	
050002-E-1	Projector Stand	$2,012.00	

(Includes installation and A2LA accredited calibration)

5% OFF 5% off all Main Units

+

5% OFF 5% off all Packages

+

Installation & Calibration Included



M172868-41

PH-3515 Profile Projector, M2 Software/ Hardware and All-In-One Touchscreen PC

Compatible Digital-Read-Out (DRO) Devices

KA-200 Counter: PH-3515 & PV-5110


MeasurLink® ENABLED
Data Management Software by Mitutoyo



Display unit for X & Y Linear Scales

- ABSOLUTE and incremental modes (10 presets each)
- 0.05-.0001mm / .02" - .000005" in resolution
- Calculator functionality

M2 Software & Hardware: PH-3515 & PJ-PLUS




MeasurLink® ENABLED
Data Management Software by Mitutoyo

Now offering M2 V2 with added measurement analysis capabilities.

- 2D Coordinate Measurement Software
- Programable Measurement Procedures
- Statistical Analysis
- Full integration & A2LA Calibration Included

Automatic Edge Detection



Fiber Optic Edge Detection system integrated into M2 software via M2 Communication Unit.

Intuitive Edge Teach Functionality built into software.

Allows for continuous measurement of features, while storing data for post process analysis.

PJ-Plus with M2 2D Processor Packages

The PJ-Plus is a new series of profile projectors offered by Mitutoyo. This system utilizes LED lighting and a fanless design making it ideal for harsh manufacturing facilities or job shops.

Order No.	Description	XY Stage	List	Promo
PJ-PLUS Main Units - 5% Off				
302-801-10A	PJ-P1010A 4x4"/100x100m	4x4"/100x100m	Request a Quote	
302-802-10A	PJ-P2010A 8X4"/200x200mm	8X4"/200x200mm		
PJ-PLUS & M2 Packages - 5% Off				
302-801-10A-M2	PJ-PLUS 4x4 - M2 and Touchscreen PC Package	4x4"/100x100mm	Request a Quote	
302-801-10A-M2-EDGE	PJ-PLUS 4X4 - M2, Optical Edge Detection and Touchscreen	4x4"/100x100mm		
302-802-10A-M2	PJ-PLUS 8x4 - M2 and Touchscreen PC Package	8x4"/200x100mm		
302-802-10A-M2-EDGE	PJ-PLUS 8x4 - M2, Optical Edge Detection and Touchscreen	8x4"/200x100mm		
Machine Stand (Optional)			List	
050002-E-1	Projector Stand		$2,012.00	

Effective September 21 through December 18

5% OFF 5% off all Main Units

+

5% OFF 5% off all Packages

+

Installation & Calibration Included



302-801-10A-M2-EDGE

MeasurLink® ENABLED
Data Management Software by Mitutoyo

An XY axis digital counter is built into the PJ-Plus



PV-5110 Vertical (Downward) Profile Projector (5% OFF Main Unit & 5% OFF DRO)

The PV-5110 Profile Projector is a downward optical axis projector fitted with a stable glass stage for delicate item inspection, ensuring accuracy and preventing damage. Its advanced optics and secure platform make it an optimal choice for precise applications, particularly with thin or delicate workpieces.

- ø19.4" Screen, Vertical Projector.
- Downward Optical Axis - Provides improved oblique surface illumination.
- LED illumination.
- Built-In Dual Oblique Surface Illumination for improved contrast.

5% OFF 5% off all Main Units

+

5% OFF 5% off all Packages


+

Installation & Calibration Included



Order No.	Description	List	Promo
PV-5110 Main Unit & Digital Readout Interface Packages - 5% Off			
304-919-11A-KA	PV-5110 with KA Counter	Request a Quote	
304-919-11A-QM	PV-5110 with QM Data		
304-919-11A-QM-OPT	PV-5110 with QM Data and Optoeye		

PLEASE NOTE: No stand or elevated surface is required.



304-919-11A-KA
PV-5110 with KA Counter

Additional DRO

QM Data: PH-3515, PJ-PLUS, PV-5110 & PJ-H30



The QM-Data200 unit features the powerful QM 2D coordinate measurement software pre-loaded onto our rugged user interface. The QM-Data200 interface features easy-to-use key operations and allows for measurement results to be visualized on its LCD Display.

MeasurLink ENABLED
Data Management Software by Mitutoyo



Plot Single Data Points



Return 2-Dimensional Graphic and Calculated Values

- Built-In Guided Measurement Tutorials.
- Programmable Measurement Procedures & Calculations.
- Data Collection and USB Output.
- Full Integration and A2LA Calibration conducted by Mitutoyo Field Service team.

Optoeye-200

Optical Edge Detection
(Additional Purchase Required)



PJ-H30 High Accuracy Vertical Profile Projector

The Mitutoyo PJ-H30 is unique given its ability to produce an uninverted image, improving intuitive operation as the projected image appears in the same orientation as the workpiece.

- Optical system with high NA lenses provides bright and high contrast images
- The three-lens mounting turret includes a 10X lens as standard
- Built-in digital XY Counter

303-716-13A &
264-131-13A-PJH-OPT



Order No.	Description	XY Travel	List	Promo
PJ-H30 Main Units - 5% OFF				
303-716-13A	PJ-H30A1010B	4x4"/100x100mm	Request a Quote	
303-717-13A	PJ-H30A2010B	8x4"/200x100mm		
303-718-13A	PJ-H30A2017B	8x6.7"/200x170mm		
303-719-13A	PJ-H310A3017B	12x6.7"/300x170mm		
Digital Readout Interface (Add-On Packages - Optional) - 5% Off				
264-161-13A-PJH	QM-DATA200 Arm Type (PJ-H Series Package)		Request a Quote	
264-161-13A-PJH-OPT	QM-DATA200 Arm Type & Optoeye (PJ-H)			
Machine Stand (Optional)			List	
050002-E-1	Projector Stand		$2,012.00	


5% OFF 5% off all Main Units

+

5% OFF 5% off all Packages

+

Installation & Calibration Included



MeasurLink ENABLED
Data Management Software by Mitutoyo

303-717-13A PJ-H30A2010B

Measuring Reimagined.

QM-Fit

Precision at the Speed of Touch

Measure faster, easier, and anywhere with this compact desktop smart measuring system. Just place your workpiece and instantly capture multiple dimensions with ±10 µm, accuracy, no focusing, no fuss. Its touch-panel control and table-top footprint make high-precision measurement simple, quick, and accurate.

- Ideal for users of profile projectors and hand measuring tools.
- Wide field of view and spacious stage for easy workpiece setup.
- Large batch measurement capability.
- Operates with only a single power cord, no external PC required.
- Automatically extracts multiple measurement elements from the image in one shot.




Package	Description
359-752-13	QM-Fit with Mitutoyo Installation & Calibration

Accuracy spec based on controlled environment (20 °C ±1 ° C)

IMPROVED EFFICIENCY IN MEASURING INTRICATE PARTS

Advanced element recognition provides intelligent and efficient dimensional measurement. The intuitive touch panel makes accurate and reliable measurements easy for anyone to perform. Developed with our end users' requests in mind, this system perfectly meets the needs of demanding industrial environments.



Workpieces can be measured instantly, simply by placing them on the measuring stage.




Effective September 21 through December 18

Automatic Element Detection

Detects multiple elements at once.

Automatically recognizes and detects circles, lines, and more with just one tap. Measurements can be performed quickly without the need to specify elements one by one in advance.





Detected elements have their outline color changed.


QM-Fit

SMART VISION SYSTEM - Compact Vision Measuring Machine

NEW FEATURES








Midline / Midpoint:

Create and measure midpoints, midlines, and intersection points.







Distance between circles:

Circle-Circle Shortest Distance and Longest Distance

Intersections:

Create and measure intersections using circular and line elements:


- Intersection of circle and circle
- Intersection of line and circle

NEW FEATURES

Procedure Recording

Simply place the workpiece for automatic inspection.

Even if workpieces are randomly placed on the measuring stage, it can quickly recognize their shape, identify the workpiece, and immediately begin measurement. Creating procedures is as easy as measuring a single workpiece.




No need to push a button. Different workpieces are automatically recognized and measured.

Pass/Fail Judgment

Pass/fail checks at a glance.

By entering nominals and tolerances, the measurement results are displayed as ✓ (pass) or ✕ (fail), allowing quick judgment at a glance.



1 SMART 2 INSTINCTIVE 3 COMPACT

Quick Image

A double telecentric optical system with a large depth of focus, quick release stage, and a large selection of stage sizes make the Quick Image a high-efficiency VMM.

- Manual or motorized stages available.
- High pixel count color camera.
- Automatic part location with pattern search tool.
- CAD file overlay.
- Profile of a line built in.
- Stitching function allows for measurements of parts larger than the field of view.

Package	Model No.	Stage Size	List	Promo
361-850M3PK	QI-A1010D	4″ x 4″	Request a Quote	
361-851M3PK	QI-A2010D	8″ x 4″		
361-852M3PK	QI-A2017D	8″ x 7″		
361-853M3PK	QI-A3017D	12″ x 7″		
361-854M3PK	QI-A4020D	16″ x 8″		

Packages include machine, PC, software, installation, A2A accredited calibration, and online training
* Manual Stage

Installation & Calibration Included
+
Online Training Course Included






M3 Software

An intuitive and thoughtful icon-driven user interface, a flexible probe library, and powerful tolerancing and programming make M3 the perfect solution for the Quick Image system.

- Includes profile
  - Allows profile of a line comparing measured points to a nominal CAD file
- Includes DXF overlay
  - Overlay a CAD file, similar to a profile projector overlay
- Includes image stitching
  - Measure large parts by combining multiple fields of view into a single image
- Includes pattern search
  - Automatically locate and measure a part regardless of size or orientation
- Includes program finder
  - Automatically identify a part and load the corresponding part program
- Includes multi-measure
  - Measure multiple features by drawing a box around them

Effective September 21 through December 18

Errors due to height are greatly minimized with a depth of focus up to 22mm. Measurement errors due to human focusing are eliminated.



Measuring a stepped workpiece

Installation & Calibration Included

+

Online Training Course Included




Package	Model No.	Stage Size	List	Promo
361-860-11M3PK	QI-C2010D	8″ x 4″	Request a Quote	
361-861-11M3PK	QI-C2017D	8″ x 7″		
361-862-11M3PK	QI-C3017D	12″ x 7″		

Packages include machine, PC, software, installation, A2A accredited calibration, and online training
*Motorized Stage

Auto-Recognition

Use pattern search for multiple workpieces within the screen view, and measure them all in one operation with a single touch or mouse click. This eliminates the need for accurate positioning of workpieces and cumbersome setup of fixtures.




Multiple pattern search

Simultaneous measurement of patterns

Optional Thread Module

Adds the ability to inspect external thread features and quickly calculate the Outside and Root Thread Diameters, the Pitch Diameter, the Lead, and the Root and Crest Truncation values.

Order No.	Package	List	Promo
64VIS002	LF-TM	Request a Quote	



MF Measuring Microscopes with Metlogix M2 Software and Touch-Screen Tablet

Featuring M2 geometric measuring display

- Highest measuring accuracy in its class.
- Quick release mechanism and zero-set buttons on stage controls increase operability when working on larger workpieces.
- Easy-to-use all-in-one PC touch ccreen display.
- M2 Geometric 2D measurment software & interfacing retrofit available.
- Camera port is standard on all models.
- Wide range of objectives available from 1x to 100x.

MeasurLink® ENABLED
Data Management Software by Mitutoyo

172-864-10 - MF-A3017, LED, BINOCULAR TUBE, 64PKA-M2-MF - M2 Software/ Hardware



20% OFF

MF-U Measuring Microscopes


- Measuring accuracy that is highest in its class (and conforms to JIS B 7153).
- Quick release mechanism and zero-set buttons on stage controls increase operability when working with large workpieces.
- Compatible with all Mitutoyo M Plan Infinity Corrected Optics.
- Optional manual or motorized turrets available.
- M2 Geometric 2D measurment software & interfacing retrofit available.
- Promoted units stage travel ranges from 200mm x 100mm to 300 x 170mm

20% OFF

176-878-10 MF-UB2017D - with 64PKA-M2-MF - M2 Software/ Hardware







MeasurLink® ENABLED
Data Management Software by Mitutoyo

64PKA-M2-MF
M2 Retrofit Kit for MF/MF-U Microscopes

M2 is a universal 2D coordinate measurement software which has become the preferred software for many optical comparator users due to its intuitive user interface and data collection procedures.

- Software & All-In-One Touch Screen PC Included
- Full Integration and A2LA Calibration conducted

Discounted Microscope Main Units

LIMITED SUPPLY - WHILE SUPPLIES LAST

Order No.	Description	List	Promo
176-864-10	MF-A3017D 300x170mm | BrightField Manual Microscope	Request a Quote	
176-878-10	MF-UB2017D 200x170mm | Infinity Corrected, Bright Field, 3-Axis, Manual		
176-879-10	MF-UB3017D 300x170mm | Infinity Corrected, Bright Field, 3-Axis, Manual		
176-886-10	MF-UD1010D 100x100mm | Infinity Corrected, Bright Field & Dark Field, 3-Axis, Manual		
176-887-10	MF-UD2010D 200x100mm | Infinity Corrected, Bright Field & Dark Field, 3-Axis, Manual		
176-888-10	MF-UD2017D 200x170mm | Infinity Corrected, Bright Field & Dark Field, 3-Axis, Manual		
176-889-10	MF-UD3017D 300x170mm | Infinity Corrected, Bright Field & Dark Field, 3-Axis, Manual		

*illumination Unit Sold Separately
*While Supplies Last

Installation & Calibration Included

Effective September 21 through December 18

TM Toolmakers' Microscopes

- Adjustable illumination intensity.
- Angle measurement is performed easily by turning the angle scale disc to align the cross-hair reticle with the workpiece image.
- Includes standard accessories which create an overall magnification of 30X. Magnifications can be changed from 20X - 200X by using optional objectives and/or eyepieces.
- .000050" Resolution Digimatic micrometer heads included.

MeasurLink® ENABLED
Data Management Software by Mitutoyo



Newly designed LED illumination



TM-A505B
176-820-11A

Model No.		TM-A505B	TM-A1005B
Order No.		176-820-11A	176-821-11A
Eyepiece		Standard accessory: 15X (field number: 13), Options: 10X, 20X	
Objective lens		Standard accessory: 2X, Options: 5X, 10X	
Microscope head	Maximum height of workpiece	4.53" / 115mm	4.21" / 107mm
Illumination unit	Transmitted illumination	Stepless brightness adjustment, White LED light source, with green filter	
	Surface illumination	Oblique single-source type, Stepless brightness adjustment, White LED light source	
Cross-travel stage	Measuring range	2" x 2" / 50×50mm	4" x 2" / 100×50mm (An optional 2"/50mm gage block is required to cover full range. A CERA block is recommended.)
	Usable area of the stage glass	3.8" x 3.8" / 96×96mm	6" x 3.8" / 154×96mm
	Maximum stage glass loading	11 lbs. / 5kg	
Linear measurement method		Micrometer heads included	
List		$8,730.00	$11,344.00
Promo		$8,294.00	$10,777.00



Order No.	Description
64PMI247	MOTICAM S1, 1.2 MEGAPIXEL-1/3" CMOS, USB
64PMI249	MOTICAM S3, 3.0 MEGAPIXEL-1/2" CMOS, USB
64PMI248	MOTICAM S6, 6.0 MEGAPIXEL-1/1.8" CMOS, USB
64PMI252	MOTI-CAM 4000, 8 MEGAPIXEL, 1/1.8" CMOS , USB/HDMI
63AAA060	.37x C-Mount Eyetube Adapter

Trinocular Stereo Microscope SMZ143-N2LED

- Continuous 1X - 4X magnification.
- Image always in focus throughout zoom range.
- Crisp, erect images with high resolution and excellent stereoscopic effect.
- Stereo-tube can be rotated a full 360° for viewing at any angle.
- Bilateral zoom control knob adds convenience and increases operator efficiency.
- Diopter adjustment for both eyepieces.

Model Order No.	MSM-414TL 377-993A
Optical tube	Trinocular head
Total magnification	10X - 40X
Eyepiece	Widefield WF10X/20mm
Objective	1X - 4X
Working distance	80mm
Field of view	20mm - 5mm
Dimensions	237x170x335mm
Mass	6.2kg



Order No.	Description	List	Promo
Stereo Microscope Unit			
377-993A	MSM-414TL TRINOCULAR MICROSCOPE	Request for Quote	
Observational Camera Accessories			
377-481	C-mount Video Adapter for SMZ143-N2LED	$83.00	$79.00
64PMI309	MOTICAM 4000X, 1.45 x 1.45µm PIXEL, HDMI / USB MULTIPOINT	$3,924.00	$3,728.00

*377-481 and 64PMI252 purchased separately



Camera with software for digital viewing

Surftest SJ-220 Packages

MeasurLink® ENABLED
Data Management Software by Mitutoyo

- NEW 2.8" color touch screen makes navigation and measuring condition settings easier to perform.
- The built-in battery charges via USB Type-C has approximately 1,000 measurements on a full charge (4 hours charging time).
- Performs roughness analysis conforming to international standards JIS '82 / JIS '94 / JIS '01 / ISO '97 /ANSI/VDA including ISO21920.
- Optional MicroSD card can store up to 500 measurement conditions, 10,000 measurement results and 500 image data.
- New [HOME] key lets the operator easily recall frequently used calibration and measurement conditions.

NEW Products

OVER 10% OFF



178-742-13

ASK US ABOUT OUR SJ-220 ELEARNING COURSE

Order No.	Description	List	Promo
178-742-13	Surftest SJ-220 Standard drive unit type 4mN inch	$4,212.00	$3,791.00
12AAA221	Adapter, Magnetic Stand, Dia. 8mm	$72.00	$65.00
12AAA233	Adapter, Height Gauge, 1/4" X 1/2"	$162.000	$146.00
178-069	Stand, SJ-210/310/410	$1,602.00	$1,442.00
178-602DCAL	Roughness Specimen, IN/MM, W/Certificate	$428.93	$386.00
264-628	WIRELESS UNIT FOR MEASURING INST U-WAVE-TIB	$422.00	$380.00
570-413	HEIGHT GAUGE, DIGIMATIC, ABSOLUTE LINEAR ENCODER 0-18", .0005" / 0-450MM, 0.01MM	$1,544.00	$1,390.00


12AAA233


12AAA233


570-413


178-069




12AAA221

Wireless connectivity now available for increased measurement data


With Wireless Unit for Measuring Instrument U-WAVE-TIB installed




Bidirectional communication (BLE communication)



Effective September 21 through December 18

This is a user-friendly device that provides compatibility and versatility to meet diverse manufacturing needs.



Example of combination with Height Gage




When used in combination with a Height Gage, a variety of measurements can be performed.

Dedicated app "SJ-App" for increased efficiency of measurement work

The dedicated app that enables communication with the SJ-220 is equipped with various functions to increase work efficiency.
It is also possible to manage data, create inspection reports, and export to CSV and PDF files on the terminal.

Smartphone icon display



*Example


Startup screen



Calculation result





Inspection report



Added convenience by linking to PC with highly functional free software, "SJ-Communication-Tool"

We provide free software that allows you to import various data (measurement conditions, parameter settings, calculation results, measurement data) from the SJ-220 to create and edit inspection reports on your PC. This software can significantly reduce the time it takes to create reports.





Confirmed operation environments

■ OS: Windows 10 (64 bit), Windows 11 (64 bit)

* Windows is a product of Microsoft Corporation.

* Connection requires a USB 2.0 Cable or a Wireless Unit for Measuring Instrument U-WAVE-TIB.

Heavy Load Hardness Testers - HV Series

Highly Versatile Basic Model

20% OFF






HV-110/120 System A

- Equipped with a high performance motorized test force selection function and motorized turret mounts.
- Operates as smoothly as electric models but with the certainty of traditional test forces.
- A list function makes it easy to perform multi-point and average hardness evaluations which required extra effort or external data processors with conventional manual models. This convenient screen enables consistency of test results.
- Motorized test force selection and motorized turret positions can be easily controlled via a touch screen control panel. Adjustable X-Y stage with built-in digital micrometers for detailed measurement analysis.

Model	Test Force									Order No.	Body	List	Promo
HV-110	V.S*	HV1	HV2	HV3	HV4	HV5	HV10	HV20	HV50	810-440-13	HV-110 - TYPE A - MANUAL BODY IN/MM SPECIFICATION	Request a Quote	
	N	9.807	19.61	29.52	49.03	98.07	196.10	294.2	490.3				
	kgf	1	2	3	5	10	20	30	50				
HV-120	V.S*	HV 0.3	HV 0.5	HV1	HV2.5	HV5	HV10	HV20	HV30	810-445-13	HV-120 - TYPE A - MANUAL BODY IN/MM SPECIFICATION		
	N	2.942	4.903	9.807	24.51	49.03	98.07	196.1	294.2				
	kgf	0.3	0.5	1	2.5	5	10	20	30				

*V.S - Vickers Scale

*Additional Components Required for a Complete System



20% OFF

Installation & Calibration Included

HV-110/120 System B,D

- B and D series testers feature AVPAK dedicated image software enabling automatic indentation reading with excellent automatic edge detection capability, reducing reading variation and visual error.
- D series testers add powered X-Y stages which enable automatic continuous testing. This allows extended multi-point testing, complex pattern creation and multiple workpiece analysis to be carried out automatically.
- D series testers add Auto Focus and create a fully automatic system that dramatically shortens the cycle time of your test and indentation analysis.

Model	Test Force									Order No.	Body	List	Promo
HV-110	V.S*	HV1	HV2	HV3	HV4	HV5	HV10	HV20	HV50	810-443A	HV-110 - TYPE B/D - BODY IN/MM SPECIFICATION	Request a Quote	
	N	9.807	19.61	29.52	49.03	98.07	196.10	294.2	490.3				
	kgf	1	2	3	5	10	20	30	50				
HV-120	V.S*	HV 0.3	HV 0.5	HV1	HV2.5	HV5	HV10	HV20	HV30	810-448A	HV-120 - TYPE B/D - BODY IN/MM SPECIFICATION		
	N	2.942	4.903	9.807	24.51	49.03	98.07	196.1	294.2				
	kgf	0.3	0.5	1	2.5	5	10	20	30				

*V.S - Vickers Scale

*Additional Components Required for a Complete System

Effective September 21 through December 18

Micro Vickers Hardness Testers - HM Series

- HM Type A systems include a built-in measuring eyepiece for indentation analysis and accurate workpiece positioning.
- Automatic Turret (Touch-screen controlled in Type A systems and software controlled via AVPAK in Type B and D systems).
- Test force range 10g-1000g (HM-210) and .05-2000g (HM-220).
- LED illumination.
- Type B and D systems include a camera for software analysis (Type A systems can use optional camera for digital imagery).
- Type A and B systems use micrometer-controlled adjustable stages and Type D systems utilize a motorized XY Stage.

20% OFF



64AAB308PA
HM-210B Type System

Installation & Calibration Included

20% OFF MICRO VICKERS TESTERS!

MeasurLink® ENABLED
Data Management Software by Mitutoyo

Functions	System A	System B	System D
			
Focusing	Manual	Manual	Automatic
Testing Action	Single Point	Single Point	Pattern Specific
Test-point Positioning	Manual X-Y Stage	Manual X-Y Stage	Automatic X-Y Stage
Measuring Indentations	Manual Monoscope	Automatic by AVPAK	Automatic by AVPAK
Camera (for observing and measuring indentations)	600,000 Pixels B&W*	Color, 3 Million Pixels	Color, 3 Million Pixels
Operating the Main Unit	Touch Panel	PC**	PC**



*PC Sold Separately

** PC sold separately

*Additional packages available. Please contact your local Mitutoyo distributor or Mitutoyo sales representative.

Discounted Testers

Order No.	Description	List	Promo
64AAB307P	HM220 VICKERS HARDNESS TESTER, TYPE A	Request a Quote	
64AAB308P	HM220 VICKERS & KNOOP HARDNESS TESTER, TYPE A		
64AAB323PA	HM-210 VICKERS HARDNESS TESTER, TYPE B		
64AAB324PA	HM-210 VICKERS & KNOOP HARDNESS TESTER, TYPE B		
64AAB325P	HM-220 VICKERS HARDNESS TESTER, TYPE B		
64AAB326P	HM-220 VICKERS & KNOOP HARDNESS TESTER, TYPE B		
64AAB380PA	HM-210 VICKERS HARDNESS TESTER, TYPE D		
64AAB381PA	HM-210 VICKERS & KNOOP HARDNESS TESTER, TYPE D		
64AAB382P	HM-220 VICKERS HARDNESS TESTER, TYPE D		
64AAB383P	HM-220 VICKERS & KNOOP HARDNESS TESTER, TYPE D		

Rockwell and Rockwell Superficial Hardness Tester

With Real-Time Electronic Test Force Control

- Closed-loop control of testing forces.
- Initial and Total test forces (loads) are applied with unparalleled accuracy and repeatability.
- Extended indenter arm reaches inside diameters and hard-to-reach surfaces at eye level, allowing the operator to easily see where the indenter accesses small or hard-to-reach parts.
- Automatic cycle start after initial set point is reached.
- Continuous test mode for automatic testing of all like-sized parts.
- All hardness parameters set automatically via the touch screen.
- Cylindrical and spherical surface corrections.
- Auto conversion to most common hardness scales or tensil strength.

MeasurLink® ENABLED
Data Management Software by Mitutoyo



HR-530
810-233-33

Model No.		HR-530	HR-530L
Order No.		810-233-33	810-333-33
Hardness testing methods		Rockwell / Rockwell Superficial / Brinell / Plastics Hardness	
Initial Test Force		29.42 N (3kgf), 98.07 N (10kgf)	
Test Force (N)	Superficial	147.1 N (15kgf), 294.2 N (30kgf), 441.3 M (45kgf)	
	Rockwell	588.4 N (60kgf), 980.7 N (100kgf), 1471 N (150kgf)	
	Light Force Brinell	61.29 N (6.25kgf), 98.07 N (10kgf), 153.2 N (15.625kgf), 245.2 N (25kgf), 294.2 N (30kgf), 306.5 N (31.25kgf), 612.9 N (62.5kgf), 980.7 N (100kgf), 1226 N (125kgf), 1839 N (187.5kgf)	
Test Force Control		Automatic (load / hold / unload)	
Maximum Speciment Size		Height: 9.8" (250mm) Depth: 5.9" (150mm)	Height: 15.5" (395mm) Depth: 5.9" (150mm)
External Data Output		RS-232C, Digimatic, USB2.0	
External Dimensions	Main Unit	9.84" x 26.38" x 23.82" (250 w x 667 d x 621 h mm)	11.6" x 26.2" x 30.1" (300 w x 667 d x 766 h mm)
	Touch-Panel Display	191 w x 147 d x 71 h mm (Color)	
Mass		Approx. 60 kg	Approx. 69 kg
	List	$20,549.00	$25,291.00
	Promo	$18,494.00	$22,762.00



HR-530L
810-333-33

* Must purchase Power Cord **02ZAA010**

ASTM Compliant HR Series Rockwell and Superficial Hardness Tester Packages Include:

- Certified Blocks and Indenters
- C and N Scale Indenter
- 1/16" Carbide Ball Indenter
- HRC30 Rockwell Test Block
- HRC63 Rockwell Test Block
- HRBW95 Rockwell Test Block
- HR30N60 Rockwell Test Block
- HR30TW70 Rockwell Test Block
- Certificate stating conformance to ASTM E 18
- Mitutoyo Installation and A2LA Calibration



HR-430MR includes only diamond indenter, C-scale indenter, HRC and HRBW blocks listed above

Calibration Set

Order No.	Order No.	Order No.	Order No.
64HAA462	64HAA463	64HAA464	64HAA465
HRC Scale	HRBW Scale	HR30N Scale	HR30TW Scale
Test Blocks	Test Blocks	Test Blocks	Test Blocks
64HAA181	64HAA172	64HAA270	64HAA303
64HAA177	64HAA170	64HAA266	64HAA301
64HAA173	64HAA168	64HAA262	64HAA299
Universal Style Indenter with Flat			
64HAA100	64HAA119	64HAA101	64HAA119

SCAN ME

Effective September 21 through December 18

A Complete Line of ASTM Compliant Rockwell Hardness Testing Machines

10% OFF 10% off all Packages

+

FREE SHIPPING Free Shipping

+

Installation & Calibration Included







	HR-320MS	HR-430MR	HR-430MS	HR-610A/HR-620A	HR-620B
Rockwell Scales		x			
Rockwell and Superficial	x		x	x	x
Dead Weight	x	x	x		
Individual Hanging Weights	x				
Dial Weight		x	x		
Automatic break		x	x		
Closed Loop				x	x
Digital Display	x	x	x	x	x
7.1" Max Sample Height	x	x	x		
9.8" Max Sample Height				x	x
15.5" Max Sample Height					
6.5" Max Depth	x	x	x		
5.9" Max Depth					
8.6" Max Depth				x	x
CNC					x
Motorized X Stage (Optional)				x	x
Motorized Y Stage					x
Software Control and Analysis					x
ASTM Compliant HR Series Rockwell & Rockwell Superficial Packages - All 10% Off	810-192-21	810-193-21	810-194-31	810-512-23 (HR610A) or 810-522-23 (HR620A)	810-527-21
List	$12,622.00	$14,126.00	$18,580.32	Request a Quote	**Request a Quote**
Promo	$11,359.80	$12,713.40	$16,722.29		

* Must purchase Power Cord **02ZAA010**

Scalable Interfacing Options



HR-320MS, HR-430MR, HR-430MS Interface



HR-530, HR-530L, HR-610A & HR-620A Touchscreen Controller



HR-620B PC Interface, Utilizing AVPAK Software

EJ Series Industrial Interface-mounted Compact Counter





Compact size and easy to use

Up to 8 compact counters (EJ counters) can be linked providing the capacity to connect up to 16 gages. On a DIN rail, each unit can be connected directly without using cables, so it takes up minimal space. All linked units and gages can be driven by a single power source.

EtherNet/IP, CC-Link, PROFINET, EtherCAT or USB Connection


Data can be output through an industrial interface by linking a compact counter (EJ counter) with an interface unit. Constant data monitoring and positional management are performed. A USB interface is also provided for easy connection with a computer.

Note: The range of interfaces is set to be expanded in the near future.

Order No.	Description	List	Promo
542-081	Main EJ Module Counter	$1,193.00	$1,133.00
542-081A	Main EJ Module w/AC Components	$1,397.00	$1,327.15
21HZA149	USB Only Interface	$730.00	$694.00
21HZA186	CC-Link Module (Mitsubishi), and USB	$1,617.00	$1,536.00
21HZA187	PROFINET Module	$1,617.00	$1,536.00
21HZA188	EtherNet/IP Module	$1,678.00	$1,594.00
21HZA264	EtherCat Module	$1,617.00	$1,536.00

Calculation function

Enables sum difference operations between 2 gages connected to the same counter. Functions such as tolerance judgment and peak hold are also included.



Linear Gage LG200 Series

- Slimmer body with approx. 1/5 cross section compared with **542-190** (**LG100**).
- High-accuracy gage head suitable for in-line and in-laboratory use.
- Assures the expected repeatability (2σ) in the full measurement range and the narrow-range precision.
- Protection grade IP67G with sliding durability of 100 million times and more and adoption of highly oil-resistant materials.
- It can be connected to a compact counter (EJ counter) suitable for in-line use or building into a device or a multifunctional counter (EH counter) suitable for use in measurement rooms.

IP67 G



542-186/542-187/542-188

Order No.	Description	List	Promo
542-186	LG200-110, Range: 0.4"/10mm, Res:.00005"/ 1µm	$1,277.00	$1,213.00
542-187	LG200-0510, Range: 0.4"/10mm, Res:.00002"/ 0.5µm	$1,374.00	$1,305.00
542-188	LG200-0110, Range: 0.4"/10mm, Res:.00005"/ 0.1µm	$1,471.00	$1,397.00

Linear Gage LG100 Series

High Accuracy

Precision and accuracy demanded by the automated assembly and inspection markets are guaranteed. Due to our expertise as a manufacturer of measuring instruments, repeatability in the full measurement range (2σ) and narrow-range precision are also guaranteed.

Environment Resistance

Sliding durability of more than 50 million cycles*, with protection level of IP67G. A highly oil-resistant material is used in the rubber cap and cable sheath so it can be used in harsh environments.

* 10 mm range models (Actual value from in-house tests)

Reference Point Detection (LG100 Series)

Reference point signal output functions are featured throughout this series. When incorporating into a device, the master setting value is easy to set and is retained after shutdown.



Order No.	Description	List	Promo
542-190	LG100-110, Range: .4"/10mm, Res: .00005"/1µm	$1,102.00	$1,047.00
542-191	LG100-0510, Range: .4"/10mm, Res: .00002"/0.5µm	$1,252.00	$1,189.00
542-192	LG100-0110, Range: .4"/10mm, Res: 5µinch/0.1µm	$1,362.00	$1,294.00
542-193	LG100-125, Range: 1"/25mm, Res: .00005"/1µm	$1,398.00	$1,328.00
542-194	LG100-0525, Range: 1"/25mm, Res: .00002"/0.5µm	$1,569.00	$1,491.00
542-195	LG100-0125, Range: 1"/25mm, Res: 5µinch/0.1µm	$1,678.00	$1,594.00
542-196	LG100-150, Range: 2"/50mm, Res: .00005"/1µm	$1,702.00	$1,617.00
542-197	LG100-0550, Range: 2"/50mm, Res: .00002"/0.5µm	$1,885.00	$1,791.50


LG QuickSetup Tool

A configuration tool is FREE for use with the EJ counter when connected via the optional USB interface. Multiple settings normally carried out with counter operating keys can now be easily applied from a computer. Live displays allow for easily viewing gage positions or measurements at a glance.

Note: This software can be used free of charge and downloaded from the Mitutoyo website.
https://www.mitutoyo.co.jp/eng/contact/products/lg/




General settings



Parameter setting

Solution for Film and Foil Thickness Measurement


The key to success:
High accuracy thickness measurement of thin foil and film samples.

- The combination of the Litematic and the vacuum plate system provides high accuracy measurement of easily deformed material.
- Litematics allow measurements at forces as low as 0.01N. The ceramic ball contact included with the Vacuum Packages will increase the force to 0.04N.
- The vacuum plate absorbs the contact-sensitive specimen, such as battery film, onto the plate surface for more stable measurement.
- Mitutoyo Canada provides vacuum plate packages as well as custom-made solutions.
- Optional set 02AZE375 enables the application of up to 10 intermediate forces.
- Data export to MeasurLink® and MS Excel®.





Vacuum Off



Vacuum On



VL-50-B



VL-50S-B

Separate Type Litematic Main Unit

Order No.	Model	Test Force*	List	Promo
318-226-23	VL-50S-B	0.01N	$12,088.00	$11,484.00
957460	Granite Stand		$6,853.00	$6,510.00

- Measuring accuracy (20°C) up to (0.5+L/100) µm L=arbitrary measuring length (mm).
- Repeatability up to 0.05 µm.

Stand-alone Litematic Main Unit

Order No.	Model	Test Force*	List	Promo
318-221-23	VL-50-B	0.01N	$13,990.00	$13,291.00

- Measuring accuracy (20°C) up to (0.5+L/100) µm L=arbitrary measuring length (mm).
- Repeatability up to 0.05 µm.



Vacuum Package Add-ons

Order No.	Model	List	Promo
64PKA297	50x50mm Vacuum Package	Request a Quote	
K543722	Laser-activated Vacuum Package	Request a Quote	

*The ceramic ball contact included with Vacuum Packages will add 0.03N.



Vacuum Package Add-ons

Order No.	Model	List	Promo
64PKA298	100x100mm Vacuum Package	Request a Quote	

*The ceramic ball contact included with Vacuum Packages will add 0.03N.

Effective September 21 through December 18

In-line Measuring System

LSM-02-A/30-A/CU-A

- Guaranteed repeatability:
  LSM-02-A (ø1 mm): ±0.015 µm, LSM-30-A (ø10 mm): ±0.06 µm
- Guaranteed linearity: LSM-02-A: ±0.3 µm, LSM-30-A: ±1.0 µm
- Equipped with USB Type-C, I/O ports, and optional industrial interfaces.
- Standard configuration software included for user-friendly setup.





I/F module



CC-Link IE TSN EtherNet/IP

EtherCAT PROFINET

Order No	Range	Resolution	Protocol	List	Promo
544-123	.0002" - .08" / 0.005-2mm	0.0000004"/0.01 µm	—	$10,761.00	$10,223.00
544-124	.012" - 1.18"/0.3-30mm	0.0000004"/0.01 µm	—	$11,855.00	$11,262.00
544-121	—	—	USB, Digital I/O	$5,289.00	$5,025.00
02AGQ300	—	—	EtherNet/IP	$2,250.00	$2,138.00
02AGQ350	—	—	PROFINET	$2,250.00	$2,138.00
02AGQ370	—	—	EtherCAT	$2,250.00	$2,138.00
02AGQ390	—	—	CC-Link	$2,250.00	$2,138.00

High-Accuracy Non-Contact Measuring Systems

- Excellent linearity: down to +/- 0.3 micron.
- High-speed scanning capable: 3,200 scans per second.
- Various ranges available for selecting the best laser for your application.
- Statistical calculation mode.
- Memory function has been increased to allow storage of up to 100 programs.

QUICKTOOL* is free downloadable software that makes programming the LSM-6200 quick and easy.
*For use with customer-supplied PC and optional RS-232C cable.



Package


LSM-6200 Display Unit Included

MeasurLink® ENABLED
Data Management Software by Mitutoyo

WHILE SUPPLIES LAST

Order No	Model	Range Inch	Range mm	Repeatability	Linearity	Scanning Rate	List	Promo
64PKA119	LSM-503S	.012" - 1.18"	0.3~30mm	±0.11µm	±1.0µm›	3,200 scans/sec	$18,902.00	$17,957.00
64PKA120	LSM-506S	.04" - 2.36"	1~60mm	±0.36µm	±3µm›	3,200 scans/sec	$21,820.00	$20,729.00
64PKA121	LSM-512S	.04" - 4.72"	1~120mm	±0.85µm	±6µm›	3,200 scans/sec	$34,830.00	$33,089.00

› Linearity over entire range. Higher accuracies are possible over smaller ranges.



Mitutoyo Digital Readout Packages

Mounting hardware included on all machine retrofit packages

5 Year Warranty Digital Readout Packages Mitutoyo

All DRO Packages Include:

- KA-200 Counter
- KA-200 Counter tray/arm kit
- High Resolution Linear Scales (down to .0001" or better!)
- Bracket Kit(s)

5% OFF




MeasurLink® ENABLED
Data Management Software by Mitutoyo

Linear Encoder: 5% Off

Package Order No.	Description	List	Promo
539-801N	LINEAR SCALE,AT715,4",100MM,ABSOLUTE	$773.00	$734.00
539-802R	LINEAR SCALE,AT715,6",150MM,ABSOLUTE	$619.00	$588.00
539-803R	LINEAR SCALE,AT715,8",200MM,ABSOLUTE	$418.00	$397.00
539-804N	LINEAR SCALE,AT715,10",250MM,ABSOLUTE	$779.00	$740.00
539-805N	LINEAR SCALE,AT715,12",300MM,ABSOLUTE	$779.00	$740.00
539-806N	LINEAR SCALE,AT715,14",350MM,ABSOLUTE	$789.00	$749.00
539-807N	LINEAR SCALE,AT715,16",400MM,ABSOLUTE	$802.00	$761.00
539-808N	LINEAR SCALE,AT715,18",450MM,ABSOLUTE	$816.00	$775.00
539-809N	LINEAR SCALE,AT715,20",500MM,ABSOLUTE	$824.00	$782.00
539-811N	LINEAR SCALE,AT715,24",600MM,ABSOLUTE	$839.00	$797.00
539-813N	LINEAR SCALE,AT715,28",700MM,ABSOLUTE	$852.00	$809.00
539-814N	LINEAR SCALE,AT715,30",750MM,ABSOLUTE	$869.00	$825.00
539-815N	LINEAR SCALE,AT715,32",800MM,ABSOLUTE	$874.00	$830.00
539-816N	LINEAR SCALE,AT715,36",900MM,ABSOLUTE	$953.00	$905.00
539-817N	LINEAR SCALE,AT715,40",1000MM,ABSOLUTE	$990.00	$940.00
539-818N	LINEAR SCALE,AT715,44",1100MM,ABSOLUTE	$900.00	$855.00
539-819R	LINEAR SCALE,AT715,48",1200MM,ABSOLUTE	$1,007.00	$956.00
539-820N	LINEAR SCALE,AT715,52",1300MM,ABSOLUTE	$1,091.00	$1,036.00
539-821N	LINEAR SCALE,AT715,56",1400MM,ABSOLUTE	$995.00	$945.00
539-822N	LINEAR SCALE,AT715,60",1500MM,ABSOLUTE	$1,362.00	$1,293.00
539-823N	LINEAR SCALE,AT715,64",1600MM,ABSOLUTE	$1,483.00	$1,408.00

Other packages and kits are available for mills, lathes, grinders and custom machines and applications. Contact your local distributor for details.



Accessory: 5% Off

Package Order No.	Description	List	Promo
53AAA375	COUNTER TRAY,KA	$43.00	$41.00
64AAB191	BRACKET KIT FOR LATHE	$419.00	$398.00
64AAB196	BRACKET KIT, UNIVERSAL FOR SCALE-Y	$383.00	$364.00
64AAB199	SCREW KIT	$97.00	$92.00
64AAB200	MACHINE ARM KIT FOR KA COUNTER	$325.00	$309.00

Counter: 5% Off

Package Order No.	Description	List	Promo
174-183A	KA COUNTER, 2-AXIS	$903.00	$858.00
174-185A	KA COUNTER, 3-AXIS	$1,328.00	$1,262.00

Effective September 21 through December 18

Digimatic Quill Kit


Easy Installation, Fits Most Vertical Knee Mills

- Easy-to-read LCD with resolution of .0005"/0.01mm. 0-6" travel.
- Push-button controls for inch/mm, Zero-Set and On/Off.
- Powered by a single SR-44 Battery which lasts about 1 year with normal use.
- SPC Output for data transmission to data processors or a remote display.
- ABS encoder.

Order No.	Description	List	Promo
053906B	Digimatic Quill Kit Complete with Brackets & Scale for Bridgeport Type Machines	$649.00	$617.00

SPC ABSOLUTE™

MeasurLink® ENABLED
Data Management Software by Mitutoyo



ABSOLUTE Digimatic Scale Units

- The Origin key allows setting of an ABSOLUTE zero point to be used as reference in subsequent measurements. Once set, the ABS Digimatic Scale Unit is ready to show its true position whenever turned on, rather than 0.00" as with standard models.
- The Zero/ABS key allows the display to be zero-set at any slider position along the beam for incremental comparison measurements. This key will also allow return to the ABSOLUTE coordinate with a display of the true position from the origin point.
- No rack, no pinion, no glass scale. Digimatic scale unit is safely embedded in the hardened stainless steel blade.
- Horizontal or vertical face according to the scale mounting direction.
- Multi-function types with diameter displaying function are also available for lathes. (Contact Mitutoyo.)
- All units come with two mounting brackets, each located at either end of the scale.
- With SPC data output.

SPC ABSOLUTE™




MeasurLink® ENABLED
Data Management Software by Mitutoyo


Order No.	Model	Range	Accuracy	Resolution	Type	List	Promo
572-210-30	SD-4"DX	0-4" / 0-100mm	.001" / 0.03mm	.0005" / 0.01mm	Horizontal Single-function	$491.00	$442.00
572-211-30	SD-6"DX	0-6" / 0-150mm	.001" / 0.03mm	.0005" / 0.01mm	Horizontal Single-function	$520.00	$468.00
572-212-30	SD-8"DX	0-8" / 0-200mm	.001" / 0.03mm	.0005" / 0.01mm	Horizontal Single-function	$606.00	$545.00
572-213-10	SD-12"D	0-12" / 0-300mm	.002" / 0.04mm	.0005" / 0.01mm	Horizontal Single-function	$1,170.00	$1,053.00
572-310-10	SDV-6"D	0-4" / 0-100mm	.001" / 0.03mm	.0005" / 0.01mm	Vertical Single-function	$544.00	$490.00
572-311-10	SDV-6"D	0-6" / 0-150mm	.001" / 0.03mm	.0005" / 0.01mm	Vertical Single-function	$576.00	$518.00
572-312-10	SDV-8"D	0-8" / 0-200mm	.001" / 0.03mm	.0005" / 0.01mm	Vertical Single-function	$670.00	$603.00
572-313-10	SDV-12"D	0-12" / 0-300mm	.002" / 0.04mm	.0005" / 0.01mm	Vertical Single-function	$1,289.00	$1,160.00

Applications


Machine table position



Drilling machine stroke position




Focus setting on optical instruments



Special Applications

As a measurement jig for outdoor use (SD-G)



Detector head mechanism

